

Exploring Molecular Heteroencoders with Latent Space Arithmetic: Atomic Descriptors and Molecular Operators

Xinyue Gao¹, Natalia Baimacheva² and Joao Aires-de-Sousa^{3,*}


¹ Faculty of Sciences, Université Paris Cité, 75013 Paris, France

² Faculty of Chemistry, University of Strasbourg, 4, Blaise Pascal Str., 67081, Strasbourg, France

³ LAQV and REQUIMTE, Chemistry Department, NOVA School of Science and Technology, Universidade Nova de Lisboa, 2829-516 Caparica, Portugal

* Correspondence: jas@fct.unl.pt

Figure S1: Examples of molecules transformed by H→F LSV molecular operators (each example includes the starting molecule (Start), the molecule obtained with the global rule (+ Global rule), the molecule obtained with the specific rule (+ Specific rule), the molecule obtained with the specific rule multiplied by 2 (+ Specific rule x 2), and the most similar molecule that was used to build the specific rule (Rule source)).


















Start

+ Global rule

+ Specific rule

+ Specific rule x 2

Rule source
















Start

+ Global rule

+ Specific rule

+ Specific rule x 2

Rule source



Start

+ Global rule

+ Specific rule

+ Specific rule x 2

Rule source

