

Supplementary Materials for

Dissolved organic phosphorus removal in secondary effluent

by ferrate (VI): performance and mechanism

Lei Zheng^{1,2}, Panpan Gao³, Yali Song¹, Hua Wang¹, Yang Deng^{2,*}

¹ School of Civil Engineering and Architecture, Zhejiang University of Science and Technology, Hangzhou 310023, China

² Department of Earth and Environmental Studies, Montclair State University, Montclair, NJ 07043, USA

³ School of Engineering, Hangzhou Normal University, Hangzhou 311121, China

*Corresponding author.

Prof. Yang Deng

CELS Room 220, Montclair State University, 1 Normal Ave, Montclair, NJ 07043, USA.

Email: dengy@mail.montclair.edu

Table S1 Water quality of sampled secondary effluent

Parameters	Value
pH	7.48
UV ₂₅₄ absorbance	0.161 cm ⁻¹
Turbidity	2.33 NTU
Dissolved organic carbon (DOC)	40.0 mg/L
Alkalinity	200 mg/L as CaCO ₃
Dissolved total phosphorus (DTP)	2.12 mg/L as P
Dissolved inorganic phosphorus (DIP)	2.08 mg/L as P
Total organic phosphorus (TOP)	42.0 µg/L as P
Nitrate-nitrogen (NO ₃ ⁻ -N)	2.60 mg/L
Ammonia-nitrogen (NH ₃ -N)	10.4 mg/L




Figure S1 LC-MS information of ATP (A: LC detection of pure ATP; B: MS of ATP molecule; C: MS of daughter product)