


Structure and Dielectric Behavior of $\text{Yb}_2\text{O}_3\text{-MgO}$ Co-Doped $0.92\text{BaTiO}_3\text{-}0.08(\text{Na}_{0.5}\text{Bi}_{0.5})\text{TiO}_3$ Ferroelectric Relaxor

Xiao-Hu Ren and Dong-Yun Gui *

College of Materials Science and Engineering, Xi'an University of Architecture and Technology, Xi'an 710054, Shaanxi, China; renxiaohu@xauat.edu.cn (X.-H.R.)

* Correspondence: guidy@xauat.edu.cn



Citation: Ren, X.-H.; Gui, D.-Y.; Structure and Dielectric Behavior of $\text{Yb}_2\text{O}_3\text{-MgO}$ Co-Doped $0.92\text{BaTiO}_3\text{-}0.08(\text{Na}_{0.5}\text{Bi}_{0.5})\text{TiO}_3$ Ferroelectric Relaxor. *Materials* **2021**, *14*, 6802. <https://doi.org/10.3390/ma14226802>

Academic Editor: Jan Dec

Received: 13 October 2021

Accepted: 5 November 2021

Published: 11 October 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

Figure S1. Temperature-dependent permittivity ($\epsilon_r^* = \epsilon_r' - j\epsilon_r''$) of the BT-NBT-YM samples at different frequencies. (a) BT-NBT, (b) $x = 0$, (c) $x = 0.005$, (d) $x = 0.01$, (e) $x = 0.015$, (f) $x = 0.02$, (g) $x = 0.025$.