

## Copper-Substituted Calcium Orthophosphate ( $\text{Ca}_{1-x}\text{Cu}_x$ ) $\text{HPO}_4 \cdot n\text{H}_2\text{O}$ for humidity detection

Y. Milovanov<sup>1</sup>, M. Dadkhah<sup>1</sup>, Ahmed S. Afify<sup>2</sup>, J.M. Tulliani<sup>1</sup>

<sup>1</sup> Politecnico di Torino, Department of Applied Science and Technology, INSTM R.U. Lince Laboratory, Corso Duca degli Abruzzi 24, 10129 Turin, Italy

<sup>2</sup> Department of Basic Sciences, the Higher Institute of Engineering and Automotive Technology and Energy, New Heliopolis 11829, Egypt

### Supplementary information




Figure. S1. Sensor response under 90% RH for BCu0\_10L and PVA\_10L.




Figure. S2. Sensor response under 10 ppm  $\text{CH}_4$  for BCu5\_10L.




Figure. S3. Sensor response under 500 ppm CO<sub>2</sub> for BCu5\_10L.




Figure. S4. Sensor response under 4 ppm NH<sub>3</sub> for BCu5\_10L




Figure. S5. Sensor response under 2.5 ppm NO<sub>2</sub> for BCU5\_10L