Supporting Information

Micro/Nanostructured Coating for Cotton Textiles that Repel Oil, Water, and Chemical Warfare Agents

Jihyun Kwon, Hyunsook Jung, Heesoo Jung, Juno Lee[*].

Agency for Defense Development, Yuseong-Gu, Daejeon 34186, South Korea

E-mail: juno@add.re.kr

This supplementary information includes the following sections:

Table S1. TGA and DTG data of raw and OmniBlock coated cotton fabrics in air and nitrogen.

| Atmosphere	Sample	$T_{5\%}$ (℃)	$T_{10\%}$ (℃)	T_{max1} (℃)	Residue at T_{max1} (%)	T_{max2} (℃)	Residue at T_{max2} (%)	Residue at 800 ℃ (%)
Air	Raw cotton	90	260	327	45.6	415	7.6	1.3
	OmniBlock coated cotton	192	273	324	58.2	426	19.4	9.6
Nitrogen	Raw cotton	75	273	343	46.0	-	-	16.3
	OmniBlock coated cotton	219	287	341	57.9	-	-	23.9

Figure S1. Surfaces for height of small structures of (a) raw cotton fabric and (b) OmniBlock coated cotton fabric.

**Figure S2.** SEM image of OmniBlock coated cotton fabric.

Figure S3. The optical images of (a) water droplet and (b) n-dodecane droplet on Ar plasma treated cotton fabric, (c) water droplet, and (d) n-dodecane droplet on OmniBlock coated cotton fabric

Figure S4. Optical image of HD and GD droplet onto OmniBlock coated cotton.

Figure S5. Optical images of shedding angle analysis for n-dodecane on (a) 40°and (b) 45° inclined surface.

Figure S6. The optical images of knotted (a) raw cotton fabric and (b) OmniBlock coated cotton fabric.