

Supplementary Materials

Multiple Kinetic Parameterization in a Reactive Transport Model Using the Exchange Monte Carlo Method

Ryosuke Oyanagi ^{1,*}, Atsushi Okamoto ² and Noriyoshi Tsuchiya ²


¹ Department of Solid Earth Geochemistry, Japan Agency for Marine-Earth Science and Technology (JAMSTEC), Yokosuka 237-0061, Japan

² Department of Environmental Studies for Advanced Society, Graduate School of Environmental Studies, Tohoku University, Sendai 980-8579, Japan; okamoto@mail.kankyo.tohoku.ac.jp (A.O.); tsuchiya@mail.kankyo.tohoku.ac.jp (N.T.)

* Correspondence: royanagi@jamstec.go.jp; Tel.: +81-46-867-9667

Received: 1 October 2018; Accepted: 6 December 2018; Published: 8 December 2018

(a) $\text{Log}_{10}(\sigma_y) = -2.0$



(b) $\text{Log}_{10}(\sigma_y) = -1.2$




Figure S1. Synthetic datasets with noise levels of (a) $\sigma_y = 10^{-2.0}$ and (b) $\sigma_y = 10^{-1.2}$ used in the accuracy tests. Gray lines show the values predicted using the reactive transport model (Equation (9), with the parameters described in Section 3) and the red data points are the noisy data.