



Article

Efficiency and Technological Reliability of Contaminant Removal in Household WWTPs with Activated Sludge

Agnieszka Micek ¹, Krzysztof Józwiakowski ^{1,*}, Michał Marzec ¹, Agnieszka Listosz ¹
and Tadeusz Grabowski ^{1,2}

- ¹ Department of Environmental Engineering and Geodesy, University of Life Sciences in Lublin, Leszczyńskiego 7, 20-069 Lublin, Poland; agnieszka.micek@up.lublin.pl (A.M.); michal.marzec@up.lublin.pl (M.M.); agnieszka.listosz@up.lublin.pl (A.L.); tadeusz.grabowski@up.lublin.pl (T.G.)
- ² Roztocze National Park, Plażowa 2, 22-470 Zwierzyniec, Poland
- * Correspondence: krzysztof.jozwiakowski@up.lublin.pl

Abstract: The results of research on the efficiency and technological reliability of domestic wastewater purification in two household wastewater treatment plants (WWTPs) with activated sludge are presented in this paper. The studied facilities were located in the territory of the Roztocze National Park (Poland). The mean wastewater flow rate in the WWTPs was 1.0 and 1.6 m³/day. In 2017–2019, 20 series of analyses were done, and 40 wastewater samples were taken. On the basis of the received results, the efficiency of basic pollutant removal was determined. The technological reliability of the tested facilities was specified using the Weibull method. The average removal efficiencies for the biochemical oxygen demand in 5 days (BOD₅) and chemical oxygen demand (COD) were 66–83% and 62–65%, respectively. Much lower effects were obtained for total suspended solids (TSS) and amounted to 17–48%, while the efficiency of total phosphorus (TP) and total nitrogen (TN) removal did not exceed 34%. The analyzed systems were characterized by the reliability of TSS, BOD₅, and COD removal at the level of 76–96%. However, the reliability of TN and TP elimination was less than 5%. Thus, in the case of biogenic compounds, the analyzed systems did not guarantee that the quality of treated wastewater would meet the requirements of the Polish law during any period of operation. This disqualifies the discussed technological solution in terms of its wide application in protected areas and near lakes, where the requirements for nitrogen and phosphorus removal are high.

Keywords: efficiency of contaminant removal; technological reliability; wastewater purification; activated sludge; national park



Citation: Micek, A.; Józwiakowski, K.; Marzec, M.; Listosz, A.; Grabowski, T. Efficiency and Technological Reliability of Contaminant Removal in Household WWTPs with Activated Sludge. *Appl. Sci.* **2021**, *11*, 1889. <https://doi.org/10.3390/app11041889>

Received: 29 January 2021

Accepted: 17 February 2021

Published: 21 February 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

In national parks and protected areas, there are usually museums, forester's lodges, hostels, or tourist trails with resting places for visitors, which should be equipped with sanitary infrastructure that ensures their proper functioning. According to the Law on Nature Protection [1] in Poland and the Council Directive 92/43/EEC [2], in the area of national parks and nature reserves, it is forbidden to build or reconstruct any buildings or technical facilities with the exception of facilities and devices that serve to achieve the goals of the given national park or nature reserve. For this reason, it is essential in protected areas to use water supply systems and wastewater treatment plants (WWTPs) that do not interfere with the environment [3,4] and meet the criteria of sustainable development and nature protection [5–7].

Domestic wastewater generated by various tourist facilities in national parks or protected areas, just as in rural areas, is most often discharged to non-return tanks (septic tanks) and is then taken to collective WWTPs or disposed of in individual wastewater treatment systems, i.e., in so-called small household WWTPs [8,9]. A similar way of dealing

with domestic sewage in protected and rural areas, where sewerage systems and collective treatment plants are lacking, is also in force in other countries around the world [10–19].

In recent years, household WWTPs have increasingly become one of the basic elements of technical infrastructure in protected areas where, due to natural and landscape values and large dispersion of tourist buildings, the installation of a sewerage network and a collective WWTP is not justified [9,13,14,17,19]. In accordance with Polish Standard PN-EN 12,566 [20], household WWTPs are defined as facilities for 50 inhabitants. However, on the basis to the Water Law [21], the maximum capacity of such systems in Poland should not exceed 5 m³/day.

Various technological solutions are currently used to treat small amounts of wastewater, such as systems with drainage pipes, systems with a sand filter, WWTPs with activated sludge, systems with a biological bed, hybrid systems (activated sludge + biological bed), and constructed wetland systems (CWs) [7,22].

A review of the literature on the evolution of wastewater management and its development over the centuries was presented by Lofrano and Brown [23]. Currently, the activated sludge method is the most commonly used for wastewater purification in the world. Activated sludge is most often used for urban wastewater treatment [24–27], as well as for industrial wastewater [28,29]. The popularity of the activated sludge method used in large WWTPs around the world has led to the development of “miniature” facilities of this type, whereby for over 30 years, attempts have been made to replicate the technological processes [24,30–35]. However, it is important for household WWTPs with activated sludge, which are used to treat small sewage amounts, to meet the appropriate criteria.

The most important aspects that should be considered during the selection of a technological solution involving small WWTPs are the efficiency of pollutant removal and the reliability of operation [4]. These criteria should be taken into account especially for WWTPs installed in protected areas [36]. In the case of WWTPs, efficiency refers to the degree of removal of particular types of pollutants, which is determined by the amount of pollutants retained in the system in relation to the amount of pollutants entering the system. Reliability, on the other hand, is defined as the ability to treat wastewater to the degree required by the wastewater receiver over the assumed operating time, including changes in the quantity and the composition of the inflow [32,33]. The reliability level corresponds to the probability of reaching a value of the indicator in the outflow from the WWTPs that is lower than the acceptable value; thus, reliability can be understood as the percentage of time during which the expected concentrations of pollutants in the treated wastewater are in accordance with the accepted standards or purification objectives [37,38].

The reliability and operational efficiency of activated sludge WWTPs have been previously studied by different authors [32,33,35,37,39–41]. However, there is still a lack of research results on the technological reliability of household WWTPs with activated sludge, which are analyzed over a longer period of time, especially in facilities operating in protected areas. A comprehensive analysis of the efficiency of operation of different types of WWTPs based on statistical inference and taking into account elements of reliability theory makes it possible to identify technological solutions which are characterized by the highest efficiency and stability of operation under changing conditions during many years of operation. This is important from the administrative, legal, and ecological point of view. It allows estimating the chances of passing possible control procedures, as well as establishing a hierarchy of particular technological solutions in terms of their influence on the environment. The results regarding the efficiency and reliability of household WWTP technologies should be an important element in planning the development of technical infrastructure, enabling the selection of optimal solutions under given conditions [32].

The purpose of this paper is to present the results of research on the technological reliability and the efficiency of domestic wastewater purification in two household WWTPs with activated sludge located in the area of the Roztocze National Park (RNP) in Poland. The paper contributes new content to science, because, in the world, there remain few studies related to the technological reliability of household WWTPs operating on a real scale.

2. Materials and Methods

2.1. Presentation of the Studied Facilities

The RNP is located in southeastern Poland in a temperate, transitional climate zone. Groundwater, as well as surface water, in the RNP is of a very good quality; thus, it is crucial to protect it from degradation [42]. In order to protect the quality of surface water and groundwater, in recent years, within the area of the RNP, some steps have been taken to build household WWTPs to treat wastewater outflowing from foresters' lodges.

For the analysis, two household WWTPs located in the area of the RNP were selected. The studied facilities consist of a four-chamber preliminary settling tank and a special reactor with activated sludge. They are located in Obrocz for the office building (facility no. 1) and Rybakówka for the forester's lodge (facility no. 2). The exact location of these facilities in the RNP was presented by Micek et al. [9]. The mean wastewater flow rate in the studied WWTPs was 1.0 and 1.6 m³/day, respectively. In Table 1, chosen technological parameters of the studied facilities are presented, and Figure 1 shows their technological scheme. The efficiency of pollutant removal in preliminary settling tanks, which are the first components of the selected household WWTPs in the RNP, was presented by Micek et al. [9].

Table 1. Technological parameters of the household WWTPs in the area of the RNP.

Technological Parameters	Facility No. 1—Obrocz	Facility No. 2—Rybakówka
Year of construction	2014	2014
Mean wastewater capacity Q (m ³ /day)	1.0	1.6
Volume of a septic tank (m ³)	5.7	5.7
Volume of an activated sludge chamber (m ³)	1.42	1.83
Wastewater receiver	soil	soil




Figure 1. Technological scheme of the household wastewater treatment plants (WWTPs) in the area of the Roztocze National Park (RNP) (prepared on the basis of [43]). Scheme: 1—denitrification chamber; 2—nitrification chamber; 3—separation chamber; 4—wastewater inlet; 5—tube diffuser; 6—basket grate; 7—wastewater outlet; 8—sludge outlet; 9—air distributor; 10—sludge recirculation; 11—air supply; 12—sludge recirculation; 13—air for sludge recirculation; 14—concrete foundation.

2.2. Analytical and Statistical Methods

Studies on the technological reliability and the efficiency of pollutant removal in the two chosen facilities were performed in 2017–2019. Wastewater samples for analyses were taken in different seasons (spring, summer, autumn, and winter) from (I) the four-chamber of the preliminary settling tank—after mechanical treatment, and (II) the outflow from an activated sludge chamber—after biological treatment (Figure 1).

During the study, 20 series of analyses were done and 40 wastewater samples were taken, in which parameters such as total suspended solids (TSS), biochemical oxygen demand in 5 days (BOD₅), chemical oxygen demand (COD), total nitrogen (TN), total phosphorus (TP), pH, dissolved oxygen (DO), nitrate nitrogen, nitrite nitrogen, and ammonium nitrogen were determined. Sampling, sample transportation, processing, and analyses were completed on the basis of Polish Standards of Wastewater Examination, which are compatible with the American Public Health Association—APHA [44,45]. The laboratory apparatus used to carry out the analyses was presented in another paper published by Micek et al. [9].

The obtained measurement data enabled calculating the mean, minimum, and maximum concentration of pollutant values and their standard deviation. The mean concentrations of the analyzed pollutant parameters in the influent and effluent from the WWTPs were used to determine the efficiency of pollutant removal (Figure 2).




Figure 2. Average efficiency of pollutant removal in two studied household WWTPs.

The evaluation of the technological reliability of the WWTPs was carried out using elements of Weibull’s reliability theory, which is a useful tool in assessing the risk of exceeding the normative values in wastewater discharged to the receiver [46].

The Weibull distribution is characterized by the following probability density function [46]:

$$f(x) = \frac{c}{b} \cdot \frac{x - \theta}{b}^{(c-1)} \cdot e^{-\left(\frac{x-\theta}{b}\right)^c}, \quad (1)$$

where x is a variable describing the concentration of a pollution parameter in the treated effluent, b is a scale parameter, c is a shape parameter, θ is a position parameter, and e is a constant, assuming $\theta < x$, $b > 0$, $c > 0$, and $e = 2.71828$.

A variable specifying the values of basic pollution indicators (TSS, BOD₅, COD, TN, and TP) in treated wastewater ($n = 20$) was analyzed. The analysis consisted of the estimation of the Weibull distribution parameters using the maximum-likelihood method and the verification of the null hypothesis that the analyzed variable could be

described by the Weibull distribution. The null hypothesis was verified with the Hollander–Proschan test at the significance level of 0.05 [36]. Reliability was determined from the cumulative distribution function plotted in the graphs, taking into account the normative values of the indicators specified in the Polish regulations [47] for wastewater discharged from treatment plants of up to 2000 PE (population equivalent): BOD₅—40 mg O₂·dm⁻³, COD—150 mg O₂·dm⁻³, TSS—50 mg·dm⁻³, TN—30 mg·dm⁻³, and TP—5 mg·dm⁻³. In the case of TN and TP, the values defined for wastewater discharged into lakes and their tributaries, as well as directly into artificial water reservoirs located in flowing waters, were adopted as standard values [47]. The analysis was carried out using Statistica 13.

3. Results and Discussion

3.1. The Efficiency of Pollutant Removal

The chosen statistical values of pollutants in wastewater from the studied household WWTPs are presented in Tables 2 and 3. The concentrations of pollutants in wastewater inflowing to the chambers with activated sludge (after mechanical treatment) were relevantly lower in comparison to raw wastewater flowing into the preliminary settling tanks (the first element of the system), as described in an earlier paper [9]. The values of pollutant concentrations in wastewater inflowing to the activated sludge chambers in the studied WWTPs were close to those described in the literature for wastewater treated mechanically in the preliminary settling tanks [34,35,46,48–50].

Table 2. Pollutant concentrations in the inflow and outflow of facility no. 1. TSS, total suspended solids; BOD₅, biochemical oxygen demand in 5 days; COD, chemical oxygen demand; TN, total nitrogen; TP, total phosphorus.

Parameters		Statistical Indicators							
		Mean		Min		Max		Standard Deviation	
		in	out	in	out	in	out	in	out
pH	-	-	-	7.90	6.29	8.22	7.72	-	-
Dissolved oxygen	mg O ₂ /dm ³	1.62	8.02	0.23	3.15	7.02	10.56	1.63	1.97
TSS	mg/dm ³	28.7	23.9	5.3	1.3	69.0	73.0	20.9	18.6
BOD ₅	mgO ₂ /dm ³	53.0	9.0	12.3	1.0	80.0	53.0	22.1	12.9
COD	mgO ₂ /dm ³	180	63	111	20.7	236	130	34.3	27.43
Ammonium nitrogen	mg/dm ³	136.0	39.9	111.0	15.0	172.0	80.5	17.2	18.1
Nitrate nitrogen	mg/dm ³	1.97	61.17	0.09	25.5	5.70	87.7	1.89	17.88
Nitrite nitrogen	mg/dm ³	0.31	1.36	0.03	0.59	1.17	3.97	0.43	0.81
TN	mg/dm ³	160	127	121	94	207	159	24.4	15.3
TP	mg/dm ³	12.0	11.5	8.2	9.5	17.2	19.0	3.0	2.2

TSS is a measure of the floating solid content in wastewater, which indicates its clarity [51,52]. At the researched facilities no. 1 and 2, the removal efficiency of TSS was low and amounted to 17% and 48%, respectively (Figure 2). The low efficiency of TSS removal in the analyzed systems is due to the fact that a significant proportion (>60%) is removed in the preliminary settling tanks, which constitutes the first elements of the studied WWTPs [9]. Better results for TSS removal (58–94%) were found by Marzec and Józwiakowski [31] in three facilities with activated sludge but without preliminary settling tanks. Quite high TSS removal effects (90–96%) were also obtained by Jakubaszek and Stadnik [53] in household WWTPs operating with low activated sludge technology in a sequential batch reactor (SBR) system. A study conducted on two household hybrid CW WWTPs of VF/HF type (with vertical and horizontal flow) with common reed and willow, operating in the RNP, showed that they also provide quite high efficiency (80–87%) of TSS

removal [36]. Furthermore, Marzec et al. [49], in a CW with common reed, manna grass, and Virginia mallow, obtained an efficiency of TSS removal of more than 86%.

Table 3. Pollutants concentrations in the inflow and outflow of the facility no. 2.

Parameters		Statistical Indicators							
		Mean		Min		Max		Standard Deviation	
		in	out	in	out	in	out	in	out
pH	-	-	-	7.04	6.14	11.9	7.86	-	-
Dissolved oxygen	mg O ₂ /dm ³	1.29	3.03	0.21	0.60	3.75	9.48	1.09	2.37
TSS	mg/dm ³	34.5	18.1	3.8	2.7	116	48.8	31.0	14.1
BOD ₅	mgO ₂ /dm ³	85.6	29.1	16	1.6	250	63.4	58.2	24
COD	mgO ₂ /dm ³	251	95	109	18	400	179	88	52.3
Ammonium nitrogen	mg/dm ³	97.6	53.4	58	1.1	134	102	19.7	33.0
Nitrate nitrogen	mg/dm ³	0.62	11.5	0.18	0.5	1.2	54.2	0.32	17.70
Nitrite nitrogen	mg/dm ³	0.14	0.31	0.05	0.02	0.76	1.68	0.20	0.49
TN	mg/dm ³	117	77.0	60.0	35.0	182	104	25.1	18.7
TP	mg/dm ³	17.3	12.1	11.4	9.6	30.9	15.8	5.7	2.1

The conducted study shows that the average concentrations of TSS in outflow from the analyzed WWTPs were 23.9 mg/dm³ for facility no. 1 and 18.1 mg/dm³ for facility no. 2 (Tables 2 and 3). These values are lower than the permissible value (50 mg/dm³) determined in Polish regulations [47]. However, Marzec and Józwiakowski [31] found significantly higher concentrations of TSS (55–122 mg/dm³) in the outflow from three other facilities with activated sludge but without preliminary settling tanks.

BOD₅. The efficiency of BOD₅ removal in the studied facilities no. 1 and 2 was diverse and amounted to 83% and 66%, respectively (Figure 2). Similar effects of BOD₅ removal (61–95%) were found by Marzec and Józwiakowski [31] in three other facilities with activated sludge but without preliminary settling tanks. Quite high BOD₅ removal effects (92–97%) were also obtained by Jakubaszek and Stadnik [53] in household WWTPs operating with an SBR system. Very high (98–99%) BOD₅ removal efficiency was also obtained in two hybrid household CWs of VF/HF type operating in the RNP [36]. Moreover, Marzec et al. [49] in a household CW WWTP obtained an efficiency of BOD₅ removal greater than 95%.

The average BOD₅ in outflow from the studied facilities no. 1 and 2 was 9.0 and 29.1 mg/dm³, respectively (Tables 2 and 3). These results are lower than the permissible value (40 mg/dm³) specified in Polish regulations [47]. Significantly higher BOD₅ values (24.9 to 267 mg/dm³) were found by Marzec and Józwiakowski [31] in three WWTPs with activated sludge operating without a classical mechanical stage.

COD. At the studied facilities no. 1 and 2, the COD removal efficiency was similar and amounted to 65% and 62%, respectively (Figure 2). Higher effects of COD removal (59–90%) were found by Marzec and Józwiakowski [31] in three other facilities with activated sludge without preliminary settling tanks. Similarly high COD removal effects (83–90%) were also obtained by Jakubaszek and Stadnik [53] in individual SBR systems. A study of two hybrid household CW WWTPs in the RNP showed that they also provide very high (96%) COD removal efficiency [36]. In a household hybrid CW, Marzec et al. [49] also obtained more than 95% COD removal efficiency.

The average COD values in the outflow from the analyzed facilities no. 1 and 2 were 63.0 and 95.0 mg/dm³, respectively (Tables 2 and 3). These results are lower than the permissible value (150 mg/dm³) specified in Polish regulations [47]. Marzec and Józwiakowski [31] studied some household WWTPs of similar construction to the analyzed

facilities but lacking classical preliminary settling tanks, and they found higher COD values which amounted to 128–490 mg/dm³.

Total Nitrogen. In the analyzed facilities no. 1 and 2, the efficiency of TN removal was low and amounted to 21% and 34%, respectively (Figure 2). Much lower effects of TN removal (<7%) were found by Marzec and Józwiakowski [31] in three other facilities with activated sludge without preliminary settling tanks. Significantly higher effects of TN removal (51–83%) were obtained by Jakubaszek and Stadnik [53] in household WWTPs operating with SBR systems. High TN removal effects (73–86%) were also obtained by Micek et al. [36] in hybrid household CW WWTPs of VF/HF type in the RNP. Furthermore, Marzec et al. [49], in a household hybrid CW, obtained more than 86% efficiency of TN removal.

The average values of TN concentration in the outflow from the analyzed facilities no. 1 and 2 were high and amounted to 127 and 77 mg/dm³, respectively (Tables 2 and 3). These values are several times higher than the permissible limit (30 mg/dm³) required in Poland for wastewater discharged into lakes and their tributaries [47]. Even higher concentrations of TN (124–320 mg/dm³) were previously found by Marzec and Józwiakowski [31] in the outflow from three other facilities with activated sludge but without classical preliminary settling tanks.

The efficiency of TN removal in activated sludge systems depends primarily on the course of processes such as nitrification or denitrification, among others [54,55]. From the data presented in Tables 2 and 3, it can be seen that the nitrification process in the studied facilities proceeded properly, which is evidenced by a significant decrease in the concentration of ammonium nitrogen and an increase in the content of nitrate and nitrite nitrogen, as well as the concentration of oxygen in the treated wastewater. However, high concentrations of aerobic forms of nitrogen and TN in the outflow from the analyzed systems indicate that the household WWTPs with activated sludge are not able to create appropriate conditions for the denitrification process.

Total Phosphorus. In the studied facilities no. 1 and 2, the efficiency of TP removal was low and amounted to 4% and 30%, respectively (Figure 2). Marzec and Józwiakowski [31] found higher TP removal efficiencies (3–63%) in three other activated sludge facilities without preliminary settling tanks. Higher efficiencies of TP removal (46–74%) were obtained by Jakubaszek and Stadnik [53] in household WWTPs with SBR systems. A study of two household hybrid CWs of VF/HF type operating in the RNP showed that they provide significantly higher efficiency of TP removal (90–94%) than activated sludge systems [36]. Moreover, Marzec et al. [49] achieved high TP removal efficiency (over 95%) in a household hybrid CW.

The average values of TP in the outflow from the analyzed facilities no. 1 and 2 were very high and amounted to 11.5 and 12.1 mg/dm³, respectively (Tables 2 and 3). These values are more than two times higher than the permissible value (5 mg/dm³) required in Poland for wastewater discharged into lakes and their tributaries [47]. In the outflow from three other facilities with activated sludge but without preliminary settling tanks, Marzec and Józwiakowski [31] found even higher of TP concentrations in the outflow (23.2–50.6 mg/dm³).

In the process occurring in activated sludge, phosphorus is mainly removed from wastewater via assimilation, sorption, and chemical precipitation [55]. During wastewater treatment, phosphorus is assimilated by the growing biomass and should be removed with the excess sludge. Effective biological phosphorus removal requires alternating aerobic and anaerobic conditions to allow the selection and growth of specific microorganisms that exhibit the ability to store phosphorus compounds within cells [56,57]. However, the conducted studies and observations show that the analyzed activated sludge WWTPs lack an anaerobic zone and the sludge from the secondary settling tank is not regularly removed, which probably has a negative impact on the effective removal of phosphorus from wastewater and causes its high concentrations in the outflow.

On the basis of the obtained research results and the literature review, it is concluded that household WWTPs with activated sludge provide significantly lower effects of pollutant removal than hybrid CWs, especially in terms of nutrient removal. Therefore, the authors of this paper do not recommend the widespread use of household WWTPs with activated sludge in protected areas.

3.2. Technological Reliability of the Studied Systems

The reliability of the analyzed WWTPs was determined using the Weibull method. In the first step, the distribution parameters were estimated, and the null hypothesis that empirical data can be described by a Weibull distribution was verified. The datasets were the values of the main pollutant indicators (BOD₅, COD, TSS, TN, and TP) in treated wastewater.

The determined values of the distribution parameters (θ , b , c) were consistent with the assumptions made. The null hypothesis was positively verified. The goodness of fit of the obtained distributions at the significance level of $\alpha = 0.05$ was high and was 68–98% for facility no. 1 and 51–99% for facility no. 2 (Table 4).

Table 4. Parameters of the Weibull distribution and the Hollander–Proschan goodness-of-fit test ($n = 20$).

Parameter	Parameters of Weibull Distribution			Hollander–Proschan Goodness-of-Fit Test	
	θ	c	b	Stat	p
Facility no. 1—Obrocz					
TSS	−0.2000	1.2122	28.9624	0.0217	0.9826
BOD ₅	0.9636	0.7691	10.0911	0.4015	0.6880
COD	14.6970	1.3850	80.1201	0.2532	0.8000
TN	58.8890	8.6765	132.4568	0.1400	0.8886
TP	9.4444	4.8527	12.5016	0.3000	0.7641
Facility no. 2—Rybakówka					
TSS	2.2929	1.3035	21.5361	0.1127	0.9102
BOD ₅	1.4000	1.0681	28.9343	−0.0998	0.9204
COD	−2.0000	1.8159	102.2153	−0.1191	0.9051
TN	−2.0000	3.1554	78.7167	−0.6526	0.5139
TP	−0.5000	5.5212	12.6970	−0.0081	0.9934

Symbols: stat—value of the test statistic, p —significance level of the test; when $p \leq 0.05$, the distribution of data does not obey a Weibull distribution.

The technological reliability of the studied WWTPs was determined on the basis of the distribution function (Figures 3–7), taking into account the limit values of the indicators, specified in the Regulation of the Minister of Maritime Economy and Inland Navigation [47] for WWTPs below 2000 PE.

Total suspended solids. The reliability of TSS removal in facility no. 1 was 86% (Figure 3A). On this basis, it can be concluded that, for a period of 51 days per year, the treatment plant malfunctioned. During this period, the concentration of TSS in treated wastewater exceeded the limit value (50 mg/dm³). According to Andracka and Dzienis [58], for WWTPs below 2000 PE, the minimum reliability level should be 97.3%. This means that a treatment plant of this size can malfunction for 9 days per year without adversely affecting the rating of the facility. Taking these assumptions into account, it can be concluded that, in facility no. 1, the concentration of TSS in the outflow from the analyzed WWTP was excessive for 42 days per year.




Figure 3. Weibull cumulative distribution functions and the technological reliabilities determined for TSS ((A)—facility no. 1; (B)—facility no. 2). Notation: dashed green line—reliability function, continuous green line—confidence intervals, red arrows—probability of achieving the indicators limit in the effluent.




Figure 4. Weibull cumulative distribution functions and the technological reliabilities determined for BOD₅ ((A)—facility no. 1; (B)—facility no. 2). Notation:dashed green line—reliability function, continuous green line—confidence intervals, red arrows—probability of achieving the indicators limit in the effluent.




Figure 5. Weibull cumulative distribution functions and the technological reliabilities determined for COD ((A)—facility no. 1; (B)—facility no. 2). Notation:dashed green line—reliability function, continuous green line—confidence intervals, red arrows—probability of achieving the indicators limit in the effluent.




Figure 6. Weibull cumulative distribution functions and the technological reliabilities determined for TN ((A)—facility no. 1; (B)—facility no. 2). Notation: dashed green line—reliability function, continuous green line—confidence intervals, red arrows—probability of achieving the indicators limit in the effluent.




Figure 7. Weibull cumulative distribution functions and the technological reliabilities determined for TP ((A)—facility no. 1; (B)—facility no. 2). Notation: dashed green line—reliability function, continuous green line—confidence intervals, red arrows—probability of achieving the indicators limit in the effluent.

In facility no. 2, the reliability of TSS removal was 95% (Figure 3B), indicating faulty operation of the WWTP for 19 days per year. Taking into account the previously mentioned guidelines [58], it may be concluded that the level of TSS negatively influenced the facility assessment for 10 days per year. Lower reliability levels for the analyzed indicator (about 65%) were found in some studies concerning household WWTP with activated sludge conducted by Bugajski et al. [59] and Marzec [32]. However, 100% technological reliability of TSS removal in a small sequencing batch biofilm reactor (SBBR) with activated sludge was obtained by Jucherski et al. [35]. Research on two other household hybrid CW WWTPs of VF/HF type (with vertical and horizontal flow) operating in the RNP indicated that they also provide quite high (92–100%) reliability of TSS removal [36]. Additionally, Marzec et al. [33] obtained 100% reliability of TSS removal in a household CW. On the basis of the data obtained and the literature review, it appears that activated sludge systems have lower reliability of TSS removal than CW WWTPs.

BOD₅. The technological reliability of BOD₅ removal in facility no. 1 was 95% and that in facility no. 2 was 76% (Figure 4). In facility no. 1, the level of this indicator was higher than the permissible value for 10 days a year. Similarly, in facility no. 2, the level of BOD₅ was elevated for 78 days a year.

In comparison, in a WWTP of identical design but without a preliminary settling tank, the reliability of BOD₅ reduction was 70% [32]. On the other hand, Bugajski et al. [59] in a household system Biocompact BCT S-12 determined the reliability of reducing this

indicator at the level of 88%. The BOD₅ removal reliability in a small SBBR was 77% [35]. On the other hand, maximum (100%) reliability of BOD₅ removal was reported in two other household hybrid CW WWTPs in the RNP [36]. Moreover, Marzec et al. [33] achieved 100% reliability of BOD₅ removal in a household hybrid CW.

COD. The reliability of COD removal was 96% in facility no. 1 and 87% in facility no. 2 (Figure 5). The obtained reliability levels are lower than the minimum required values given by Andracka and Dzieńnis [58]. In relation to the annual reference period, WWTP no. 1 provided the required level of organic pollutant removal expressed by COD for 359 days, while this value for WWTP no. 2 was 326 days.

The reliability indicators obtained in the analyzed activated sludge facilities in the RPN for COD are comparable to those obtained by Bugajski et al. [59] in a household WWTP working in activated sludge technology. At the same time, in the facilities in the RPN, the reliability of COD removal was higher than that found in a treatment plant based on an identical tank design but without a preliminary settling tank (60%) [32]. The reliability of COD removal in a small SBBR was 97.8% [35]. However, similarly to the case of BOD₅, maximum (100%) COD removal reliability was reported in two other household hybrid CWs WWTPs operating in the RNP [36]. Moreover, Marzec et al. [33] achieved 100% COD removal reliability in a household hybrid CW. The presented results indicate that the reliability of COD removal in household WWTPs with activated sludge is lower than that in CWs.

Total nitrogen. Both analyzed activated sludge WWTPs were characterized by extremely low reliability of TN removal. The probability that the concentration of TN in treated wastewater will not exceed the standard value (30 mg/dm³) was 0% for facility no. 1 and 5% for facility no. 2 (Figure 6).

In the case of TN removal, facility no. 1 operated deficiently throughout the whole year and provided no assurance of passing inspection procedures. On the other hand, in WWTP no. 2, above-normative values of TN in treated wastewater occurred for a period of 338 days per year. Marzec [33], while analyzing a solution identical in terms of construction, but without a classical preliminary settling tank, obtained a reliability of TN removal at the level of 24%. The reliability of TN removal in a small SBBR was only 12.2% [35]. In contrast, TN removal reliability in two other household hybrid CW WWTPs operating in the RNP was much higher and amounted to 35% and 89% [36]. On the other hand, Marzec et al. [33] obtained 94% reliability of TN removal in a household hybrid CW. The analysis of the results of the conducted study through the prism of the results reported in the literature shows that the reliability of TN removal is lower in household WWTPs with activated sludge than in CWs.

Total phosphorus. The reliability of TP removal in the tested household WWTPs with activated sludge was even lower. The probability that the content of TP in the effluent from facility no. 1 will meet the permissible value at the operator risk of $\alpha = 0.05$ was 1%. For facility no. 2, this value was determined to be 0% (Figure 7).

During the research concerning the effluent from the analyzed facilities, no cases were observed when the values were below the permissible level 5 mg/dm³ [47]. The obtained indicators allow concluding that household WWTPs with activated sludge are faulty in terms of TP removal throughout the year. The obtained results do not give a chance for a positive assessment of the facilities regarding the content of TP in treated sewage. In a similar facility, deprived of a classical mechanical treatment stage, a low technological reliability at the level of 5% was found [33]. On the other hand, the reliability of TN removal in a small SBBR was only 21.7% [35]. In contrast, a study conducted by Micek et al. [36] showed that TP removal reliability in two other household hybrid CW WWTPs operating in the RNP was much higher and amounted to 87% and 100%. Moreover, Marzec et al. [33] in a hybrid household CW achieved 100% reliability of TP removal. Similarly to other indicators, the reliability of TP removal in household WWTPs with activated sludge was lower than in CWs.

4. Conclusions

The analyzed household WWTPs with activated sludge demonstrated relatively high levels of technological reliability and efficiency regarding the removal of pollutants in terms of TSS, BOD₅, and COD. It is worth noting that the technological reliability of the analyzed systems was higher in comparison to corresponding systems with activated sludge but without a classical preliminary settling tank [32]. On this basis, it can be concluded that the modernization of the researched facilities, which included equipping them with preliminary settling tanks, brought positive effects. The use of an additional element in the form of a preliminary settling tank as the provision of a mechanical treatment stage and the extension of the retention time of wastewater in the system have improved the process of sedimentation of solids, as well as their initial biological decomposition. Unfortunately, no positive effects on the removal of biogenic compounds were observed in the studied facilities. The efficiency of nitrogen and phosphorus removal did not exceed 34%, while the levels of technological reliability oscillated below 5%. The obtained results indicate that, in the case of biogenic compounds, the researched facilities could not guarantee a quality of treated wastewater which would be consistent with the requirements specified in the Polish law during any period of their operation. This disqualifies the analyzed technological solution in terms of its wide application in protected areas and near lakes, where the requirements for nitrogen and phosphorus removal are high. On the other hand, previous research results presented in the literature indicate that hybrid constructed wetland systems are the most effective and reliable in terms of pollutant removal from domestic wastewater [36,49,50,60,61] and, therefore, should be recommended for use in protected areas.

Author Contributions: Conceptualization, K.J.; data curation, K.J. and M.M.; formal analysis, M.M. and K.J.; investigation, A.M. and A.L.; methodology, K.J.; resources, A.M. and K.J.; supervision, M.M. and A.L.; validation, K.J.; writing—original draft, A.M. and K.J.; writing—review and editing, K.J., M.M. and T.G. All authors read and agreed to the published version of the manuscript.

Funding: This paper was co-funded by the “Excellent Science” program of the Ministry of Science and Higher Education as a part of the contract no. DNK/SP/465641/2020: “The role of agricultural engineering and environmental engineering in sustainable agriculture development”.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Acknowledgments: This paper was written on the basis of research projects funded by the Polish Ministry of Science and Higher Education—project entitled “Water, wastewater, and energy management” (contracts No. TKD/DS/1, TKD/S/1, 2017–2019), the Provincial Fund for Environmental Protection and Water Management in Lublin, Poland—project entitled “Research on the optimization of the operation of household wastewater treatment plants at forest settlements in the area of Roztoczański and Poleski National Park” (contract No. TKD/OŚ/37/2018), and the Roztoczański National Park, Poland—project entitled “Performing research on the operation of six household wastewater treatment plants located at forest settlements in the Roztoczański National Park” (contract No. TKD/U-1/IŚGiE, 2019).

Conflicts of Interest: The authors declare no conflict of interest.

References

1. *The Nature Conservation Act from 16 April 2004*; Dz. U. Nr 92, Poz. 880; SEJM: Warsaw, Poland, 2004. (In Polish)
2. Philippe, S.; Paolo, G. (Eds.) *Council Directive 92/43/EEC of 21 May 1992 on the Conservation of Natural Habitats and of Wild Fauna and Flora*; Cambridge University Press: London, UK, 1992.
3. Józwiakowski, K.; Podbrożna, D.; Kopczacka, K.; Marzec, M.; Kowalczyk-Juško, A.; Pochwatka, P.; Listosz, A.; Malik, A. The state of water and wastewater management in the municipalities of the Polesie National Park. *J. Ecol. Eng.* **2017**, *18*, 192–199. [[CrossRef](#)]

4. Józwiakowski, K.; Podbrożna, D.; Kopczacka, K.; Jaguś, M.; Marzec, M.; Listosz, A.; Pochwatka, P.; Kowalczyk-Juško, A.; Malik, A. The state of water and wastewater management in the municipalities of the Roztocze National Park. *J. Ecol. Eng.* **2018**, *19*, 255–262. [[CrossRef](#)]
5. Mucha, Z.; Mikosz, J. Rational application of small wastewater treatment plants according to sustainability criteria. *Czas. Tech. Sr.* **2009**, *106*, 91–100. (In Polish)
6. Strande, L.; Weiyang, X.; Scanlon, A.; Hinckley, T.M. Evaluation criteria for implementation of a sustainable sanitation and wastewater treatment system at Jiuzhaigou National Park, Sichuan Province, China. *Environ. Manag.* **2009**, *45*, 93–104.
7. Józwiakowski, K.; Mucha, Z.; Generowicz, A.; Baran, S.; Bielińska, J.; Wójcik, W. The use of multi-criteria analysis for selection of technology for a household WWTP compatible with sustainable development. *Arch. Environ. Prot.* **2015**, *3*, 76–82. [[CrossRef](#)]
8. Józwiakowski, K.; Marzec, M.; Kowalczyk-Juško, A.; Gizińska-Górna, M.; Pytka-Woszczyło, A.; Malik, A.; Listosz, A.; Gajewska, M. 25 years of research and experiences about the application of constructed wetlands in southeastern Poland. *Ecol. Eng.* **2019**, *127*, 440–453. [[CrossRef](#)]
9. Micek, A.; Józwiakowski, K.; Marzec, M.; Listosz, A.; Malik, A. Efficiency of pollution removal in preliminary settling tanks of household wastewater treatment plants in the Roztocze National Park. *J. Ecol. Eng.* **2020**, *21*, 9–18. [[CrossRef](#)]
10. Steer, D.; Fraser, L.; Boddy, J.; Seibert, B. Efficiency of small constructed wetlands for subsurface treatment of single-family domestic effluent. *Ecol. Eng.* **2002**, *18*, 429–440. [[CrossRef](#)]
11. Brix, H.; Arias, C. The use of vertical flow constructed wetlands for on-site treatment of domestic wastewater: New Danish guidelines. *Ecol. Eng.* **2005**, *25*, 491–500. [[CrossRef](#)]
12. Puigagut, J.; Villaseñor, J.; Salas, J.J.; Becares, E.; Garcia, J. Subsurface-flow constructed wetlands in Spain for the sanitation of small communities: A comparative study. *Ecol. Eng.* **2007**, *30*, 312–319. [[CrossRef](#)]
13. Maunoir, S.; Philip, H.; Rambaud, A. Small wastewater treatment plants in mountain areas: Combination of septic tank and biological filter. *Water Sci. Technol.* **2007**, *56*, 65–71. [[CrossRef](#)] [[PubMed](#)]
14. Weissenbacher, N.; Mayr, E.; Niederberger, T.; Aschauer, C.; Lebersorger, S.; Steinbacher, G.; Haberl, R. Alpine infrastructure in Central Europe: Integral evaluation of wastewater treatment systems at mountain refuges. *Water Sci. Technol.* **2008**, *57*, 2017–2022. [[CrossRef](#)] [[PubMed](#)]
15. Seo, D.C.; DeLaune, R.D.; Park, W.Y.; Lim, J.S.; Seo, J.Y.; Do Lee, J.; Cho, J.S.; Heo, J.S. Evaluation of a hybrid constructed wetland for treating domestic sewage from individual housing units surrounding agricultural villages in South Korea. *J. Environ. Monit.* **2009**, *11*, 134–144. [[CrossRef](#)] [[PubMed](#)]
16. Ye, F.; Li, Y. Enhancement of nitrogen removal in tower hybrid constructed wetland to treat domestic wastewater for small rural communities. *Ecol. Eng.* **2009**, *35*, 1043–1050. [[CrossRef](#)]
17. Kaczor, G.; Bergel, T.; Bugajski, P.; Pijanowski, J. Aspects of sewage disposal from tourist facilities in national parks and other protected areas. *Pol. J. Environ. Stud.* **2015**, *24*, 107–114. [[CrossRef](#)]
18. Ghawi, A.H. Study on the Development of Household Wastewater Treatment Unit. *J. Ecol. Eng.* **2018**, *19*, 63–71. [[CrossRef](#)]
19. Wilk, B.; Cimochoicz-Rybicka, M. BIOVAC[®] wastewater treatment plants in the mountain national parks. *Tech. Trans.* **2018**, *1*, 113–123.
20. PN-EN 12566-3:2016-10. *Small Wastewater Treatment Plants for a Population Calculation (OLM) up to 50—Part 3: Container and/or Home Sewage Treatment Plants on Site*; Polski Komitet Normalizacyjny: Warszawa, Poland, 2016. (In Polish)
21. *Water Law. Ustawa Prawo Wodne z dnia 20 lipca 2017 r., Dz.U. 2017 poz. 1566*; SEJM: Warsaw, Poland, 2017. (In Polish)
22. Pawełek, J.; Bugajski, P. The development of household wastewater treatment plants in Poland—Advantages and disadvantages. *Acta Sci. Pol. Form. Circumiectus* **2017**, *16*, 3–14. (In Polish) [[CrossRef](#)]
23. Lofrano, G.; Brown, J. Wastewater management through the ages: A history of mankind. *Sci. Total Environ.* **2010**, *408*, 5254–5264. [[CrossRef](#)]
24. Bernardes, R.S.; Klapwijk, A. Biological nutrient removal in a sequencing batch reactor treating domestic wastewater. *Water Sci. Technol.* **1996**, *33*, 29–38. [[CrossRef](#)]
25. Bodík, I.; Kratochvíl, K.; Herdová, B.; Tapia, G.; Gašpariková, E. Municipal wastewater treatment in the anaerobic-aerobic baffled filter at ambient temperature. *Water Sci. Technol.* **2002**, *46*, 127–135. [[CrossRef](#)]
26. Di Trapani, D.; Christensso, M.; Odegaard, H. Hybrid activated sludge/biofilm process for the treatment of municipal wastewater in a cold climate region: A case study. *Water Sci. Technol.* **2011**, *63*, 1121–1129. [[CrossRef](#)]
27. Józwiakowska, K.; Marzec, M. Efficiency and reliability of sewage purification in long-term exploitation of the municipal wastewater treatment plant with activated sludge and hydroponic system. *Arch. Environ. Prot.* **2020**, *46*, 30–41.
28. Brucculeri, M.; Bolzonella, D.; Battistoni, P.; Cecchi, F. Treatment of mixed municipal and winery wastewaters in a conventional activated sludge process: A case study. *Water Sci. Technol.* **2005**, *51*, 89–98. [[CrossRef](#)] [[PubMed](#)]
29. Orhon, D.; Babuna, F.G.; Karahan, O. Industrial wastewater treatment by activated sludge. *IWA Publ.* **2009**, *8*. [[CrossRef](#)]
30. Hanna, K.M.; Kellan, J.L.; Boardman, G.D. Onsite aerobic package treatment systems. *Water Res.* **1995**, *29*, 2530–2540. [[CrossRef](#)]
31. Marzec, M.; Józwiakowski, K. Operational and environmental problems of the functioning of mini-sewage treatment plants with activated sludge. *Pol. J. Environ. Stud.* **2007**, *16 Pt III*, 525–529.
32. Marzec, M. Reliability of removal of selected pollutants in different technological solutions of household wastewater treatment plants. *J. Water Land Dev.* **2017**, *35*, 141–148. [[CrossRef](#)]

33. Marzec, M. Technological reliability of utilization of biogenic pollutants in selected technologies used in small wastewater treatment plants. *Przemysł Chem.* **2018**, *97*, 753–757. (In Polish)
34. Bugajski, P.; Kurek, K.; Józwiakowski, K. Effect of wastewater temperature and concentration of organic compounds on the efficiency of ammonium nitrogen removal in a household treatment plant servicing a school building. *Arch. Environ. Prot.* **2019**, *45*, 31–37.
35. Jucherski, A.; Walczowski, A.; Bugajski, P.; Józwiakowski, K. Technological reliability of domestic wastewater purification in a small Sequencing Batch Biofilm Reactor (SBBR). *Sep. Purif. Technol.* **2019**, *224*, 340–347. [[CrossRef](#)]
36. Micek, A.; Józwiakowski, K.; Marzec, M.; Listosz, A. Technological reliability and efficiency of wastewater treatment in two hybrid constructed wetlands in the Roztocze National Park (Poland). *Water* **2020**, *12*, 3435. [[CrossRef](#)]
37. Oliveira, S.C.; Sperling, M.V. Reliability analysis of wastewater treatment plants. *Water Res.* **2008**, *42*, 1182–1194. [[CrossRef](#)] [[PubMed](#)]
38. Alderson, M.P.; dos Santos, A.B.; Mota Filho, C.R. Reliability analysis of low-cost, full-scale domestic wastewater treatment plants for reuse in aquaculture and agriculture. *Ecol. Eng.* **2015**, *82*, 6–14. [[CrossRef](#)]
39. Eisenberg, D.; Soller, J.; Sakaji, R.; Olivieri, A. A methodology to evaluate water and wastewater treatment plant reliability. *Water Sci. Technol.* **2001**, *43*, 91–99. [[CrossRef](#)]
40. Taheriyoun, M.; Moradinejad, S. Reliability analysis of a wastewater treatment plant using fault tree analysis and Monte Carlo simulation. *Environ. Monit. Assess.* **2015**, *187*, 4186. [[CrossRef](#)]
41. Bugajski, P.; Chmielowski, K.; Kaczor, G. Reliability of a collective wastewater treatment plant. *J. Ecol. Eng.* **2016**, *17*, 143–147. [[CrossRef](#)]
42. Michalczyk, Z.; Kovalchuk, I.; Chmiel, S.; Głowacki, S.; Chabudziński, Ł.; Kharkevych, V.; Voloschyn, P. Waters. In *Roztocze. Nature and Human*; Grabowski, T., Harasimuk, M., Kaszewski, B.M., Kravchuk, Y., Eds.; Roztoczański Park Narodowy: Zwierzyniec, Poland, 2015; pp. 103–122. (In Polish)
43. Czerwieniec, D.; Trych, P. Technical Projects. Household Wastewater Treatment Plants for the Roztocze National Park. MILAGROS. Przedsiębiorstwo Realizacji Inwestycji. *Typescript*, 2004. (In Polish)
44. American Public Health Association (APHA). *Standard Methods for Examination of Water and Wastewater*, 18th ed.; American Public Health Association: Washington, DC, USA, 1992.
45. American Public Health Association (APHA). *Standard Methods for Examination of Water and Wastewater*, 21st ed.; American Public Health Association: Washington, DC, USA, 2005.
46. Józwiakowski, K.; Bugajski, P.; Mucha, Z.; Wójcik, W.; Jucherski, A.; Natawny, M.; Siwiec, T.; Mazur, A.; Obroślak, R.; Gajewska, M. Reliability of pollutions removal processes during long-term operation of one-stage constructed wetland with horizontal flow. *Sep. Purif. Technol.* **2017**, *187*, 60–66. [[CrossRef](#)]
47. *Regulation of the Minister of Maritime Economy and Inland Navigation of 12 July 2019 on Substances Which Are Particularly Harmful to the Aquatic Environment and the Conditions to Be Met When Discharging Wastewater into Water or Soil and When Discharging Rainwater or Snowmelt into Water or Water Installations*, Pos. 1311; Minister of Maritime Economy and Inland Navigation: Warsaw, Poland, 2019.
48. Bugajski, P.; Pawelek, J.; Kurek, K. Concentrations of organic and biogenic pollutants in domestic wastewater after mechanical treatment in the aspect of biological reactor design. *Infrastruct. Ecol. Rural Areas* **2017**, 1811–1822. [[CrossRef](#)]
49. Marzec, M.; Józwiakowski, K.; Dębska, A.; Gizińska-Górna, M.; Pytka-Woszczyło, A.; Kowalczyk-Juško, A.; Listosz, A. The efficiency and reliability of pollutant removal in a hybrid constructed wetland with common reed, manna grass, and Virginia Mallow. *Water* **2018**, *10*, 1445. [[CrossRef](#)]
50. Marzec, M.; Gizińska-Górna, M.; Józwiakowski, K.; Pytka-Woszczyło, A.; Kowalczyk-Juško, A.; Gajewska, M. The efficiency and reliability of pollutant removal in a hybrid constructed wetland with giant miscanthus and Jerusalem artichoke in Poland. *Ecol. Eng.* **2019**, *127*, 23–35. [[CrossRef](#)]
51. Johal, E.; Walia, B.S.; Saini, M.S.; Jha, M.K. Efficiency assessment and mathematical correlation development between BOD₅ and other parameters in Jalandhar Sewage Treatment. *Int. J. Innov. Sci. Eng. Technol.* **2014**, *3*, 13088–13096.
52. Showkat, U.; Najar, I.A. Study of efficiency of sequential batch reactor (SBR)-based sewage treatment plant. *Appl. Water Sci.* **2019**, *9*, 1–10. [[CrossRef](#)]
53. Jakubaszek, A.; Stadnik, A. Efficiency of sewage treatment plants in the sequential batch reactor. *Civ. Environ. Eng. Rep.* **2018**, *28*, 121–131. [[CrossRef](#)]
54. Ding, S.; Bao, P.; Wang, B.; Zhang, Q.; Peng, Y. Long-term stable simultaneous partial nitrification, anammox and denitrification (SNAD) process treating real domestic sewage using suspended activated sludge. *Chem. Eng. J.* **2018**, *339*, 180–188. [[CrossRef](#)]
55. Myszograj, S. Mechanisms of biological processes in domestic wastewater treatment plants. *Civ. Environ. Eng. Rep.* **2018**, *28*, 177–192. [[CrossRef](#)]
56. Quansheng, D.; Qixing, C.; Zehui, L.; Shouwei, Z. Application of microbial technology in wastewater treatment. *Prog. Appl. Microbiol.* **2017**, 23–28.
57. Bunce, J.T.; Ndam, E.; Ofiteru, I.D.; Moore, A.; Graham, D.W. A review of phosphorus removal technologies and their applicability to small-scale domestic wastewater treatment systems. *Front. Environ. Sci.* **2018**, *6*, 1–15. [[CrossRef](#)]
58. Andraka, D.; Dzienis, L. Required reliability level of wastewater treatment plants according to European and Polish regulations. *Zesz. Nauk. Politech. Białostockiej Ser. Inżynieria Sr.* **2003**, *16*, 24–28. (In Polish)

-
59. Bugajski, P.; Wałęga, A.; Kaczor, G. Application of the Weibull reliability analysis of household sewage treatment plant. *Gaz Woda I Tech. Sanit.* **2012**, *2*, 56–58. (In Polish)
 60. Jucherski, A.; Nastawny, M.; Walczowski, A.; Józwiakowski, K.; Gajewska, M. Assessment of the technological reliability of a hybrid constructed wetland for wastewater treatment in a mountain eco-tourist farm in Poland. *Water Sci. Technol.* **2017**, *75*, 2649–2658. [[CrossRef](#)] [[PubMed](#)]
 61. Wojciechowska, E.; Gajewska, M.; Ostojki, A. Reliability of nitrogen removal processes in multistage treatment wetlands receiving high-strength wastewater. *Ecol. Eng.* **2017**, *98*, 365–371. [[CrossRef](#)]