



Article

A Novel Decoupled Synchronous Control Method for Multiple Autonomous Unmanned Linear Systems: Bounded L_2 -Gain for Coupling Attenuation

Yinsheng Li , Bing Wang *  and Yuquan Chen

College of Energy and Electrical Engineering, Hohai University, Nanjing 211100, China; 15150693623@139.com (Y.L.); cyq@mail.ustc.edu.cn (Y.C.)

* Correspondence: icekingking@hhu.edu.cn

Featured Application: This proposed method is suitable for the cooperative consensus control of various homogeneous Multiple Autonomous Unmanned linear systems, such as an underwater robot swarm and aerial UAV swarm.

Abstract: This paper addresses the distributed optimal decoupling synchronous control of multiple autonomous unmanned linear systems (MAUS) subject to complex network dynamic coupling. The leader–follower mechanism based on neighborhood error dynamics is established and the network coupling term is regarded as the external disturbance to realize the decoupling cooperative control of each agent. The Bounded L_2 -Gain problem for the network coupling term is formulated into a multi-player zero-sum differential game. It is shown that the solution to the multi-player zero-sum differential game requires the solution to coupled Hamilton–Jacobi (HJ) equations. The coupled HJ equations are transformed into an algebraic Riccati equation (ARE), which can be solved to obtain the Nash equilibrium of a multi-player zero-sum game. It is shown that the bounded L_2 -Gain for coupling attenuation can be realized by applying the zero-sum game solution as the control protocol and the ultimately uniform boundedness (UUB) of a local neighborhood error vector under conservative conditions is proved. A simulation example is provided to show the effectiveness of the proposed method.

Keywords: synchronous control; multiple autonomous unmanned linear systems; bounded L_2 -gain; multi-player zero-sum game; coupling attenuation; coupled Hamilton–Jacobi equation; nash equilibrium; algebraic Riccati equation



Citation: Li, Y.; Wang, B.; Chen, Y. A Novel Decoupled Synchronous Control Method for Multiple Autonomous Unmanned Linear Systems: Bounded L_2 -Gain for Coupling Attenuation. *Appl. Sci.* **2022**, *12*, 7551. <https://doi.org/10.3390/app12157551>

Academic Editor: Luigi Fortuna

Received: 31 May 2022

Accepted: 25 July 2022

Published: 27 July 2022

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2022 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

1. Introduction

In the field of multi-agent distributed control, synchronous cooperative control is one of the most popular research topics because of its wide application prospects in many engineering systems, such as the cooperative control of autonomous underwater vehicles, wind farm and unmanned aerial vehicles. A great deal of research has been developed on the distributed control methods for multi-agent synchronization [1–4]. The purpose of distributed synchronous control is to design a control protocol for each agent, depending only on the states of neighboring agents, to ensure that the states of all agents in the communication digraph finally achieve synchronization. A leader–follower mechanism is the most popular one for distributed synchronous control because of its simplicity and scalability. The basic idea is that a leader agent is set as the reference node, and other agents are set as the follower nodes whose goal is to track the reference node to achieve the ultimate synchronization of the entire communication network.

On the basis of this mechanism, ref. [5] defines the local neighborhood error of each agent and deduces that this is a dynamical system with multiple control inputs, from itself and all of its neighbors. This means that the local neighborhood error of each agent is the

result of coupling from adjacent node agents, which brings considerable complexity to the design of the control protocol. Ref. [6] formulated this intricate relationship as a differential game, namely, a multi-agent differential graphical game, by defining a local performance index for each agent. Optimal control and game theory [7,8] has been successfully utilized to formulate strategic behavior, where the dynamic of each agent relies on the actions of itself and its neighbors. In an optimal control and differential graphical game, each agent minimizes the performance objective (cost value function) by adjusting its control strategy to optimal. In [9], the finite-time optimal coordination problem of multi-agent systems (MASs) is investigated. The authors in [10] addressed the centralized optimal coordination problem under tree formation constraints. In [11], the robust optimal formation control of heterogeneous MASs is studied. These published graphical games and optimal control methods for consensus and synchronization are achieved based on the solution of coupled Hamilton–Jacobi–Isaacs (HJI) equations and Hamilton–Jacobi–Bellman (HJB) equations, respectively. In practice, coupled HJI and coupled HJB equation are difficult to be solved by analytical methods due to their inherent nonlinearity and uncertainty.

The reinforcement learning (RL) method is often regarded as the effective method to solve the coupled HJI and coupled HJB equation. RL is the branch of machine learning concerned with how to methodically adjust the control strategy of agents based on the rewards from the environment [12–15]. In [16], an online distributed optimal adaptive algorithm is proposed for a differential graphical game, the intelligent identifier is designed to find the unknown dynamic and the neural actor–critic network structure is introduced to find the solutions of the Nash equilibrium. In [17], the bounded L_2 -gain consensus problem for the MASs with external disturbance is formulated into the zero-sum differential game by introducing a specific performance index and a policy iteration (PI) algorithm-based RL is provided to find the solution to the coupled HJI equations. In [18], the optimal synchronization control problem is studied for homogeneous MASs with input saturation by using the RL methods. This research utilizes the neural network as an approximator and a design-specific update law so that the neural network approximates the optimal value function and optimal control strategy with certain precision. However, the strict asymptotic convergence proof of the neural network is not given in these works, and only the boundedness of approximate errors is guaranteed. In addition, the neural network approximator-based RL needs to satisfy the persistence of the excitation condition (PE) [19–23], which also limits the practical engineering application of these methods.

The quadratic optimal control problem of a linear single system can be solved by solving an algebraic Riccati equation (ARE) [24], but the optimal control problem of MASs is far more complicated than that of a single system owing to the state coupling in the control design. At present, some optimal control methods of MASs are accompanied by a huge amount of calculations and strong assumptions.

Motivated by the above discussion, this paper focuses on the optimal cooperative control of Multiple Autonomous Unmanned linear systems (MAUS) from a new perspective, i.e., the adjacent nodes' input coupling part is regarded as the external disturbance. Thus, the complex distributed multi-agent error dynamics are decoupled into centralized multi-input dynamics. Inspired by the idea of a zero-sum game in [17], this paper formulates these centralized multi-input dynamics into multiple independent multi-player zero-sum differential games. The motivation is to realize the decoupled optimal synchronous control of MASs and the main contributions of this paper are listed in the following:

- (1) The coupling among the distributed multi-agents is equivalent to the disturbance from different channels, and the local neighborhood error dynamics of each agent are modeled as an independent centralized multi-player game.
- (2) The bounded L_2 -gain problem for coupling attenuation is introduced and is formulated into a multi-player zero-sum game by defining a modified performance index. Different from the L_2 -gain problem of [17], concerning disturbance rejection, the motive of the bounded L_2 -gain for the coupling attenuation studied here is to suppress the coupling effect on the performance.

- (3) It is proved that the solution of the zero-sum game requires the solution of the coupled Hamilton–Jacobi (HJ) equation. The coupled HJ equation of each agent is transformed into an independent equivalent algebraic Riccati equation, which simplifies the solution process effectively.

This paper is organized as follows. Section 2 provides the mathematical background and derives the local error dynamics of each node that is coupled by its own control protocol and those of its neighbors. Section 3 proposes the problem formulation of the bounded L_2 -gain for coupling attenuation and its equivalent multi-player zero-sum differential game. Section 4 transforms this zero-sum differential game into the solution of an algebraic Riccati equation and proves the ultimately uniform boundedness of the local neighborhood error, conservatively. The simulation results and conclusion is presented in Sections 5 and 6, respectively.

2. Preliminaries and Problem Formulation

2.1. Graph Theory

In this paper, the multi-agent directed communication network is depicted. A directed connected graph is defined as $G(V, E, A)$, where $V = \{v_1, v_2, \dots, v_n\}$ represents a finite non-empty set of nodes, $E \subseteq V \times V$ is the ordered set of nodes pairs and $A = [a_{ij}]$ is the adjacency matrix. If node v_i can receive the information from node v_j , then the node pairs $\bar{v}_{ij} = (v_i, v_j) \in E$, and node v_j is called a neighbor of node v_i . The neighbor set of node v_i is represented by $N_i = \{v_j | (v_i, v_j) \in E\}$. Correspondingly, the adjacency matrix element $a_{ij} = 1$ when $v_j \in N_i$, otherwise $a_{ij} = 0$. The graph Laplacian matrix is defined as $L = D - A$, whose row sums are equal to zero [25]. Diagonal matrix $D = \text{diag}(d_i)$ is the in-degree matrix, where $d_i = \sum_{j \in N_i} a_{ij}$ is the in-degree of node v_i .

Definition 1. A directed graph is called as strongly connected if there is a directed path for any a pair of distinct nodes (v_i, v_j) , where the directed path is the edge sequence $(v_{i1}, v_{i2}), (v_{i2}, v_{i3}), \dots, (v_{ik}, v_j)$.

Definition 2 [17]. A directed tree is a connected graph where every node except the root node, has an in-degree equal to one. The graph is called to have a spanning tree if a subset of the node pairs constructs a directed tree.

In this paper, $\bar{\lambda}(B)$ and $\underline{\lambda}(B)$ represent the maximum and minimum singular values of the matrix B , respectively.

2.2. Problem Formulation

Considering the Multiple Autonomous Unmanned linear systems (MAUS) constructed by the directed communication graph $G(V, E, A)$ having N agents, the dynamics of each agent is described in the following:

$$\dot{x}_i = Ax_i + Bu_i \quad (1)$$

where $x_i \in R^n$, $u_i \in R^{m_i}$ are states and control inputs of node i , respectively. The cooperative control of homogeneous systems is investigated in this paper and the leader node $x_0 \in R^n$ is set to satisfy the following dynamic

$$\dot{x}_0 = Ax_0 \quad (2)$$

The problem of MAUS synchronization is designing control protocols u_i for each agent so that states of each node track the leader node, i.e., $\|x_0 - x_i\| \rightarrow 0, \forall i$.

The neighborhood error for each node is defined as [26]

$$\delta_i = \sum_{j \in N_i} a_{ij}(x_i - x_j) + g_i(x_i - x_0) \quad (3)$$

where $g_i \geq 0$ denotes the pinning gain and there is at least one node that has a link to the leader node.

For the neighborhood error (3), the overall neighborhood error vector of graph $G(V, E, A)$ is given by

$$\delta = ((L + \bar{G}) \otimes I_n)(x_i - \underline{x}_0) \quad (4)$$

where $x = [x_1^T x_2^T \cdots x_N^T]^T$ and $\delta = [\delta_1^T \delta_2^T \cdots \delta_N^T]^T$ denote the global state vector and global error vector, respectively. Moreover, for $\underline{x}_0 = \underline{I}x_0 \in R^{nN}$ with $\underline{I} = 1_N \otimes I_n \in R^{nN \times n}$, I_n denotes the n dimensional identity matrix and 1_N denotes the N -vector of ones. The symbol \otimes is the Kronecker product [27]. $\bar{G} = \text{diag}(g_1, g_2, \dots, g_N)$ as a diagonal matrix represents the connection between all agents and the leader node.

The overall synchronization error is

$$\varepsilon = (x - \underline{x}_0) \in R^{nN} \quad (5)$$

Assumption 1. The communication graph is strongly connected, i.e., there is a directed path for any a pair of distinct nodes.

On the basis of Assumption 1, if $\bar{G} \neq 0$, then $g_i \neq 0$ for at least one. In this case, the matrix $L + \bar{G}$ is non-singular and the real parts of all eigenvalues are positive [26]. The following lemma can be obtained, which shows that the overall neighborhood error vector δ is positively correlated with the overall synchronization error ε .

Lemma 1. If the communication graph is strongly connected and $\bar{G} \neq 0$, the synchronization errors are bounded, as follows

$$\delta / \bar{\lambda}(L + \bar{G}) \leq \|\varepsilon\| \leq \delta / \underline{\lambda}(L + \bar{G}) \quad (6)$$

Furthermore, $\delta \equiv 0$ if and only if all nodes are synchronized, i.e.,

$$\varepsilon = (x - \underline{x}_0) = 0 \quad (7)$$

The dynamics of the local neighborhood tracking errors are given as

$$\dot{\delta}_i = \sum_{j \in N_i} a_{ij}(\dot{x}_i - \dot{x}_j) + g_i(\dot{x}_i - \dot{x}_0) \quad (8)$$

Substituting (1) and (2) into the above equation, it can be obtained that

$$\dot{\delta}_i = A\delta_i + (d_i + g_i)B_i u_i - \sum_{j \in N_i} a_{ij}B_j u_j \quad (9)$$

It can be seen that the dynamics of the local neighborhood error of each agent i is affected by multiple control inputs from node i and its adjacent nodes. The whole MAUS with the communication graph $G(V, E, A)$ presents a complex coupling relationship. It is quite intricate to solve the optimal control problem of dynamic (9) affected by multi-coupling.

3. Multi-Player Zero-Sum Differential Game for Decoupled Multi-Agent System

3.1. The Bounded L_2 -Gain Problem for Coupling Attenuation of Multi-Agent System

For decoupling, the inputs from adjacent nodes in the dynamics (9) are replaced by the virtual coupling actions $w_i(t) = [\widehat{u}_j^T]_{j \in N_i}^T$ which is regarded as the external disturbances. The performance output is defined as $z_i(t) = [\delta_i^T u_i^T]^T$. It is desired to designed the

control protocol u_i to achieve synchronization while satisfying the follow bounded L_2 -gain condition for the coupling actions with a given $\gamma_i > 0$

$$\begin{aligned} \int_0^T \|z_i(t)\|^2 dt &= \int_0^T (\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i) dt \\ &\leq \gamma_i^2 \int_0^T \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j dt + \beta(\delta_i(0)) \end{aligned} \quad (10)$$

where, $\beta(\cdot)$ is a bounded function such that $\beta(0) = 0$, $Q_i > 0$, $R_{ii} > 0$, $R_{ij} > 0$. γ_i^* is defined as the minimum value of γ_i while the bounded L_2 -gain condition (10) is satisfied.

3.2. Multi-Player Zero-Sum Differential Game

The following equation is used to define the following performance index function for each agent.

$$J_i(\delta_i(0), u_i, \widehat{u}_{-i}) = \frac{1}{2} \int_0^\infty \delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j dt \quad (11)$$

where \widehat{u}_{-i} denotes the virtual coupling control inputs from neighboring nodes, i.e., $\widehat{u}_{-i} = \{ \widehat{u}_j | j \in N_i \}$. It should be noted that the main difference from [17] is that the coupling control inputs from neighboring nodes are regarded as the virtual external disturbances directly, which greatly simplifies the design of the control protocol u_i .

The solution for the bounded L_2 -gain problem for coupling attenuation depicted in Section 3.1 can be equivalent to the Nash equilibrium solution of the multi-player zero-sum game-base on the performance index function (11). That is

$$V_i(\delta_i(0)) = \min_{u_i} \max_{\widehat{u}_{-i}} J_i(\delta_i(0), u_i, \widehat{u}_{-i}) \quad (12)$$

In this multi-player zero-sum game, the goal of u_i is to minimize the value $V_i(\delta_i(0))$. On the contrary, the virtual coupling inputs \widehat{u}_{-i} are assumed to maximize the value. This game has a unique solution if a game-theoretic saddle point $(u_i^*, \widehat{u}_{-i}^*)$ exists, i.e.,

$$V_i^*(\delta_i(0)) = \min_{u_i} \max_{\widehat{u}_{-i}} J_i(\delta_i(0), u_i, \widehat{u}_{-i}) = \max_{\widehat{u}_{-i}} \min_{u_i} J_i(\delta_i(0), u_i, \widehat{u}_{-i}) \quad (13)$$

Accordingly, the value $V_i^*(\delta_i(0))$ in the above equation is the value of the zero-sum game and satisfies the following Nash equilibrium condition for all policies u_i, \widehat{u}_{-i}

$$J_i(\delta_i(0), u_i^*, \widehat{u}_{-i}) \leq J_i(\delta_i(0), u_i, \widehat{u}_{-i}) \leq J_i(\delta_i(0), u_i, \widehat{u}_{-i}^*) \quad (14)$$

When the policies u_i, \widehat{u}_{-i} are selected, the value function of node i can yield

$$V_i(\delta_i(t), u_i, \widehat{u}_{-i}) = \frac{1}{2} \int_t^\infty \delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j dt \quad (15)$$

Differential equivalents to each value function are given as

$$\begin{aligned} 0 &= \frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) \\ &\quad + \nabla V_i^T (A \delta_i + (d_i + g_i) B_i u_i - \sum_{j \in N_i} a_{ij} B_j \widehat{u}_j), V_i(0) = 0, i \in N \end{aligned} \quad (16)$$

where $\nabla V_i = \frac{\partial V_i}{\partial \delta_i} \in R^n$ denotes the gradient vector. The Hamiltonian functions are defined as follows,

$$H_i(\delta_i, \nabla V_i, u_i, \widehat{u}_{-i}) \equiv \frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) + \nabla V_i^T (A \delta_i + (d_i + g_i) B_i u_i - \sum_{j \in N_i} a_{ij} B_j \widehat{u}_j) \quad (17)$$

Under certain policies u_i, \widehat{u}_{-i} , the partial differential equation $H_i(\delta_i, \nabla V_i, u_i, \widehat{u}_{-i}) = 0$ has a unique solution $V_i(\delta_i)$. The principle of optimality gives

$$\begin{aligned} \frac{\partial H_i(\delta_i, \nabla V_i, u_i, \widehat{u}_{-i})}{\partial u_i} &= 0 \Rightarrow u_i = -(d_i + g_i) R_{ii}^{-1} B_i^T \nabla V_i \\ \frac{\partial H_i(\delta_i, \nabla V_i, u_i, \widehat{u}_{-i})}{\partial \widehat{u}_j} &= 0 \Rightarrow \widehat{u}_j = -\frac{1}{\gamma_j^2} a_{ij} R_{ij}^{-1} B_j^T \nabla V_i, j \in N_i \end{aligned} \quad (18)$$

If the V_i^* is the Nash equilibrium solution of the multi-player zero-sum game, that is

$$V_i^*(\delta_i) = \min_{u_i} \max_{\widehat{u}_{-i}} J_i(\delta_i, u_i, \widehat{u}_{-i}) \quad (19)$$

we can obtain

$$\min_{u_i} \max_{\widehat{u}_{-i}} H_i(\delta_i, \nabla V_i^*, u_i, \widehat{u}_{-i}) = 0 \quad (20)$$

Substituting the optimal strategy determined by (18) into (20), the coupled Hamilton–Jacobi (HJ) equations yield

$$\begin{aligned} 0 &= \frac{1}{2} \delta_i^T Q_i \delta_i + \frac{1}{2} (d_i + g_i)^2 \nabla V_i^T B_i R_{ii}^{-1} B_i^T \nabla V_i - \frac{1}{2 \gamma_i^2} \sum_{j \in N_i} a_{ij}^2 \nabla V_i^T B_j R_{ij}^{-1} B_j^T \nabla V_i \\ &+ \nabla V_i^T (A \delta_i - (d_i + g_i)^2 B_i R_{ii}^{-1} B_i^T \nabla V_i + \frac{1}{\gamma_i^2} \sum_{j \in N_i} a_{ij}^2 B_j R_{ij}^{-1} B_j^T \nabla V_i), V_i(0) = 0, i \in N \end{aligned} \quad (21)$$

For a given solution V_i^* , in order to define $u_i^* = u_i(V_i^*)$ and $\widehat{u}_j^* = \widehat{u}_j(V_i^*)$ in the same way as (18), (21) can be written as

$$H_i(\delta_i, \nabla V_i^*, u_i^*, \widehat{u}_{-i}^*) = 0, V_i^*(0) = 0 \quad (22)$$

Lemma 2. For any policies u_i, \widehat{u}_{-i} , the following equation holds

$$H_i(\delta_i, \nabla V_i^*, u_i, \widehat{u}_{-i}) = \frac{1}{2} (u_i - u_i^*)^T R_{ii} (u_i - u_i^*) - \sum_{j \in N_i} \frac{\gamma_j}{2} (\widehat{u}_j - \widehat{u}_j^*)^T R_{ij} (\widehat{u}_j - \widehat{u}_j^*) \quad (23)$$

Proof of Lemma 2. Substituting u_i, \widehat{u}_{-i} for $u_i^*, \widehat{u}_{-i}^*$ in (22)

$$\begin{aligned} H_i(\delta_i, \nabla V_i^*, u_i, \widehat{u}_{-i}) &= \nabla V_i^{*T} (A \delta_i + (d_i + g_i) B_i u_i - \sum_{j \in N_i} a_{ij} B_j \widehat{u}_j \\ &+ (d_i + g_i) B_i u_i^* - (d_i + g_i) B_i u_i^* - \sum_{j \in N_i} a_{ij} B_j \widehat{u}_j^* + \sum_{j \in N_i} a_{ij} B_j \widehat{u}_j^*) \\ &+ \frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) \\ &+ \frac{1}{2} \left(u_i^{*T} R_{ii} u_i^* - u_i^{*T} R_{ii} u_i^* - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^{*T} R_{ij} \widehat{u}_j^* + \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^{*T} R_{ij} \widehat{u}_j^* \right) \end{aligned} \quad (24)$$

Substituting $H_i(\delta_i, \nabla V_i^*, u_i^*, \widehat{u}_{-i}) = 0$ into (24), we can obtain

$$\begin{aligned} H_i(\delta_i, \nabla V_i^*, u_i, \widehat{u}_{-i}) &= \nabla V_i^{*T} ((d_i + g_i)B_i(u_i - u_i^*) - \sum_{j \in N_i} a_{ij}B_j(\widehat{u}_j - \widehat{u}_j^*)) \\ &\quad + \frac{1}{2}(u_i^T R_{ii}u_i - u_i^{*T} R_{ii}u_i^*) - \frac{1}{2} \left(\gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^{*T} R_{ij} \widehat{u}_j^* \right) \end{aligned} \quad (25)$$

Completing the squares in (25) gives (23) upon the relationship between $u_i^*, \widehat{u}_{-i}^*$ and ∇V_i^* . \square

Remark 1. The policies \widehat{u}_{-i} in Section 3 are not the real policies of neighboring nodes. These are only defined as the virtual coupling input from neighboring nodes, which are regarded as the external disturbances and have the same channels as the control inputs of neighboring nodes. In this way, the bounded L_2 -gain attenuation for the real coupling inputs from neighboring nodes can be realized. In addition, the complex relationships among agents are decoupled virtually during the control protocol design process, and the solving process of zero-sum game is effectively simplified. The coupled HJ equation of each agent is independent of each other.

4. Solution to Bounded L_2 -Gain Problem for the Coupling Attenuation and the Equivalent Algebraic Riccati Equation

4.1. Solution to Bounded L_2 -Gain Problem for Coupling Attenuation

In this subsection, the control policy u_i is found to guarantee the condition (10) holds for a prescribed $\gamma_i > 0$ and $\widehat{u}_{-i} \in L_2[0, \infty)$. The following Theorem 1 shows that the solution of a coupled HJ equation (22) is actually the solution to the bounded L_2 -gain problem for coupling attenuation.

Theorem 1. Let $\gamma_i \geq \gamma_i^*$. Suppose the coupled HJ equation (22) has a smooth positive definite solution $V_i^* > 0, i \in N$. The control policy is selected as $u_i^* = u_i(V_i^*)$, given by (18) in terms of V_i^* . The bounded L_2 -gain condition (10) holds for all $\widehat{u}_{-i} \in L_2[0, \infty)$.

Proof of Theorem 1. According to Lemma 2

$$\begin{aligned} H_i(\delta_i, \nabla V_i^*, u_i, \widehat{u}_{-i}) &= \frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) + \frac{dV_i^*}{dt} \\ &= \frac{1}{2} (u_i - u_i^*)^T R_{ii} (u_i - u_i^*) - \sum_{j \in N_i} \frac{\gamma_i}{2} (\widehat{u}_j - \widehat{u}_j^*)^T R_{ij} (\widehat{u}_j - \widehat{u}_j^*) \end{aligned} \quad (26)$$

Selecting $u_i = u_i^*$, we can obtain that

$$\begin{aligned} &\frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) + \frac{dV_i^*}{dt} \\ &= - \sum_{j \in N_i} \frac{\gamma_i}{2} (\widehat{u}_j - \widehat{u}_j^*)^T R_{ij} (\widehat{u}_j - \widehat{u}_j^*) \leq 0 \end{aligned} \quad (27)$$

Integrating (27) yields,

$$\begin{aligned} &\frac{1}{2} \int_0^T \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j \right) dt \\ &\quad + V_i^*(\delta_i(T)) - V_i^*(\delta_i(0)) \leq 0 \end{aligned} \quad (28)$$

V_i^* is a smooth positive definite solution, i.e., $V_i^*(\delta_i(T)) \geq 0$, one has

$$\int_0^T (\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i) dt \leq \gamma_i^2 \int_0^T \sum_{j \in N_i} \widehat{u}_j^T R_{ij} \widehat{u}_j dt + V_i^*(\delta_i(0)) \quad (29)$$

Hence, the bounded L_2 -gain condition (10) for coupling attenuation is satisfied. \square

4.2. The Equivalent Algebraic Riccati Equation

It can be seen from the above results that the Nash equilibrium solution can be obtained by solving the coupled HJ equation (22). In this subsection, it will be shown that the coupled HJ equation (22) can be equivalent to an Algebraic Riccati equation (ARE).

Defining the optimal value function $V_i^* = \delta_i^T P_i \delta_i$, the corresponding optimal u_i^* and \widehat{u}_{-i}^* can be obtained as

$$\begin{aligned} u_i^* &= -2(d_i + g_i) R_{ii}^{-1} B_i^T P_i \delta_i \\ \widehat{u}_j^* &= -\frac{2}{\gamma_{ij}^2} a_{ij} R_{ij}^{-1} B_j^T P_i \delta_i, \quad j \in N_i \end{aligned} \quad (30)$$

Substituting (30) and $V_i^* = \delta_i^T P_i \delta_i$ into (21) yields

$$\begin{aligned} \delta_i^T (P_i A + A^T P_i) \delta_i + \frac{1}{2} \delta_i^T Q_i \delta_i &- 2(d_i + g_i)^2 \delta_i^T P_i B_i R_{ii}^{-1} B_i^T P_i \delta_i \\ &+ \frac{2}{\gamma_{ij}^2} \delta_i^T \left(\sum_{j \in N_i} a_{ij}^2 P_i B_j R_{ij}^{-1} B_j^T P_i \right) \delta_i = 0 \end{aligned} \quad (31)$$

The above equation can be equivalent to

$$\begin{aligned} P_i A + A^T P_i + \frac{1}{2} Q_i &- 2(d_i + g_i)^2 P_i B_i R_{ii}^{-1} B_i^T P_i \\ &+ \frac{2}{\gamma_{ij}^2} \sum_{j \in N_i} a_{ij}^2 P_i B_j R_{ij}^{-1} B_j^T P_i = 0 \end{aligned} \quad (32)$$

Defining the integrated matrix as

$$\begin{aligned} R &= \text{diag} \left(\frac{R_{ii}}{2(d_i + g_i)^2}, -\frac{\gamma_{i1}^2 R_{ij1}}{2a_{ij1}}, -\frac{\gamma_{i2}^2 R_{ij2}}{2a_{ij2}}, \dots, -\frac{\gamma_{id_i}^2 R_{ijd_i}}{2a_{ijd_i}} \right) \\ B &= [B_i B_{j1} B_{j2} \cdots B_{jd_i}], \quad j_1, j_2, \dots, j_{d_i} \in N_i \end{aligned}$$

Then, (32) can be rewritten as the ARE

$$P_i A + A^T P_i + \frac{1}{2} Q_i - P_i B R^{-1} B^T P_i = 0 \quad (33)$$

Theorem 2. Assume that all the real control policies $u_{-i} = \{u_j | j \in N_i\}$ of neighboring agents satisfy the bounded condition as follows,

$$\|u_j\|_2 = u_j^T u_j \leq \xi, \quad j \in N_i \quad (34)$$

Selecting the first equation of (30) as the control policies u_i , based on the solution of ARE (34). The local neighborhood error vector will ultimately and uniformly enter the following bounded invariant set

$$\Omega_i = \left\{ \delta_i | \|\delta_i\|_2 \leq \frac{\gamma_i^2 \xi \sum_{j \in N_i} \bar{\lambda}(R_{ij})}{2\bar{\lambda}(\bar{Q}_i)} \right\} \quad (35)$$

where $\|\delta_i\|_2$ denotes the Euclidean norm of δ_i and \bar{Q}_i is the positive definite matrix as $\bar{Q}_i = \frac{1}{2} Q_i + 2(d_i + g_i)^2 P_i B_i R_{ii}^{-1} B_i^T P_i$.

Proof of Theorem 2. Selecting the optimal positive value function $V_i^* = \delta_i^T P_i \delta_i \geq 0$, in terms of the solution of the coupled HJ equation (21), as the Lyapunov function. According to Lemma 2, the derivative of V_i^* is

$$\begin{aligned} \frac{dV_i^*}{dt} = & -\frac{1}{2} \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i - \gamma_i^2 \sum_{j \in N_i} u_j^T R_{ij} u_j \right) \\ & + \frac{1}{2} (u_i - u_i^*)^T R_{ii} (u_i - u_i^*) - \sum_{j \in N_i} \frac{\gamma_i}{2} (u_j - \hat{u}_j^*)^T R_{ij} (u_j - \hat{u}_j^*) \end{aligned} \quad (36)$$

Selecting $u_i = u_i^*$ as the first equation of (30) yields

$$\begin{aligned} \frac{dV_i^*}{dt} = & -\frac{1}{2} \delta_i^T Q_i \delta_i - 2(d_i + g_i)^2 \delta_i^T P_i B_i R_{ii}^{-1} B_i^T P_i \delta_i \\ & + \frac{\gamma_i^2}{2} \sum_{j \in N_i} u_j^T R_{ij} u_j - \sum_{j \in N_i} \frac{\gamma_i}{2} (u_j - \hat{u}_j^*)^T R_{ij} (u_j - \hat{u}_j^*) \\ & \leq -\delta_i^T \left(\frac{1}{2} Q_i + 2(d_i + g_i)^2 P_i B_i R_{ii}^{-1} B_i^T P_i \right) \delta_i + \frac{\gamma_i^2 \xi \sum_{j \in N_i} \bar{\lambda}(R_{ij})}{2} \end{aligned} \quad (37)$$

Let $\frac{dV_i^*}{dt} \leq 0$, we can realize that

$$\delta_i^T \delta_i = \|\delta_i\|_2 \geq \frac{\gamma_i^2 \xi \sum_{j \in N_i} \bar{\lambda}(R_{ij})}{2\lambda(\frac{1}{2}Q_i + 2(d_i + g_i)^2 P_i B_i R_{ii}^{-1} B_i^T P_i)} \quad (38)$$

Defining $\bar{Q}_i = \frac{1}{2}Q_i + 2(d_i + g_i)^2 P_i B_i R_{ii}^{-1} B_i^T P_i$ yields the bounded invariant set (35). \square

Remark 2. Theorem 2 shows the ultimately uniform boundedness (UUB) of the local neighborhood error vector δ_i . According to the bounded invariant sets Ω_i , the bound of δ_i can be arbitrarily small by presetting the matrix Q_i , R_{ii} and R_{ij} in the performance index function (11). In fact, this result is conservative because the term $-\sum_{j \in N_i} \frac{\gamma_i}{2} (u_j - \hat{u}_j^*)^T R_{ij} (u_j - \hat{u}_j^*)$ in $\frac{dV_i^*}{dt}$ is omitted. The real control inputs u_j of adjacent agents differ greatly from \hat{u}_j^* in fact, which guarantees the negative characterization of $\frac{dV_i^*}{dt}$. Therefore, the simulation results in the next section show that the local neighborhood error vector can converge asymptotically and uniformly to the origin.

Remark 3. In a practical application, matrix Q_i , R_{ii} and R_{ij} and parameter γ_i can be selected according to engineering performance requirements. If a high convergence speed and synchronization accuracy are required, Q_i can be selected to make its eigenvalues large; if a low control energy consumption is required, R_{ii} can be selected to make its eigenvalues large; the coupling attenuation level can be adjusted by adjusting matrix R_{ij} and γ_i . It should be noted that, Q_i , R_{ii} , R_{ij} and γ_i must satisfy the condition in Theorem 1, so that the coupled HJ equation (22) has a smooth positive definite solution $V_i^* > 0$. That is, (33) has a positive definite solution P_i .

5. Simulation Results

This section shows the effectiveness of the equivalent ARE approach described in Section 4 and Theorem 2. The simulation is realized in MATLAB/Simulink. Consider a class of Multiple Autonomous Unmanned homogeneous linear systems referring to [5] which is shown as follows

$$\dot{x}_i = Ax_i + B_i u_i$$

where $A = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}$, $B_1 = \begin{bmatrix} 2 \\ 1 \end{bmatrix}$, $B_2 = \begin{bmatrix} 2 \\ 3 \end{bmatrix}$, $B_3 = \begin{bmatrix} 2 \\ 2 \end{bmatrix}$ and $B_4 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}$, with the Leader dynamics $\dot{x}_0 = Ax_0$. The communication digraph structure is shown in Figure 1. The edge weights and the pinning gains are taken equal to 1.




Figure 1. The communication digraph structure.

The selected the weight matrices in (11) are $R_{11} = 9$, $R_{14} = 1$, $R_{22} = 9$, $R_{21} = 1$, $R_{33} = 9$, $R_{32} = 1$, $R_{44} = 9$, $R_{43} = 1$ and $Q_1 = Q_2 = Q_3 = Q_4 = \begin{bmatrix} 8 & 0 \\ 0 & 8 \end{bmatrix}$. The bounded L_2 -gain coefficient in (11) for each agent are preset as $\gamma_1 = 1.75$, $\gamma_2 = 3.75$, $\gamma_3 = 4.5$ and $\gamma_4 = 6.25$. The cooperative control protocol of each agent is implemented, as in Section 4.2, where the solution of ARE (33) is

$$P_1 = \begin{bmatrix} 4.8954 & -5.6084 \\ -5.6084 & 9.4934 \end{bmatrix}, P_2 = \begin{bmatrix} 41.9228 & -7.3129 \\ -7.3129 & 2.6742 \end{bmatrix}, P_3 = \begin{bmatrix} 14.4257 & -9.363 \\ -9.363 & 10.4565 \end{bmatrix}, P_4 = \begin{bmatrix} 17.4696 & -0.5066 \\ -0.5066 & 13.6 \end{bmatrix}.$$

Remark 4. In the process of a simulation design, the γ_i should be gradually reduced to search for a feasible and high coupling attenuation level under the premise that (33) has a positive definite solution P_i . Using the ARE solver in MATLAB, it is very convenient to solve (33) and obtain P_i . Then, the design of the coupling attenuation controller can be completed according to (30).

To elevate the Bounded L_2 -gain problem for the coupling attenuation, the following variable C_γ is introduced based on (29)

$$C_\gamma = \int_0^T \left(\delta_i^T Q_i \delta_i + u_i^T R_{ii} u_i \right) dt - \gamma_i^2 \int_0^T \sum_{j \in N_i} u_j^T R_{ij} u_j dt - V_i^*(\delta_i(0)) \quad (39)$$

That is, $C_\gamma \leq 0$, which means that the Bounded L_2 -gain condition (10) is satisfied.

The local neighborhood error vector of each agent is shown in Figure 2. Figure 3 is the 3-D phase plane plot of the system's evolution for agents 1, 2, 3, 4 and leader 0. The C_γ of the node 1 agent is shown in Figure 4. As can be seen from Figures 2 and 3, the neighborhood error vector can converge asymptotically and uniformly to the origin and all agents in the communication digraph are eventually synchronized, which is also consistent with Remark 2. Figure 4 shows that C_γ is always negative, which is equivalent to that the node 1 agent satisfies the bounded L_2 -gain condition with $\gamma_1 = 1.75$ for the coupling attenuation. The effectiveness of the proposed method is thus verified.




Figure 2. The local neighborhood error vector of each agent: (a) The node 1 agent; (b) The node 2 agent; (c) The node 3 agent; (d) The node 4 agent.




Figure 3. The 3-D phase plane plot of the system's evolution for agents 1, 2, 3, 4 and leader 0.




Figure 4. The C_γ of node 1 agent.

6. Conclusions

This paper provides a novel idea for the synchronization control of Multiple Autonomous Unmanned linear systems, in which the local neighborhood error dynamic's coupling part is considered as the virtual external disturbance, so as to decouple the multi-agent cooperative control problem into a relatively independent bounded L_2 -gain problem for coupling attenuation. The optimal control theory and differential game theory is utilized to formulate the bounded L_2 -gain problem into a centralized multi-player zero-sum game. It is shown that the solution to the multi-player zero-sum game is equivalent to the solution of a coupled HJ equation. It is also shown that the coupled HJ equation can be transformed into an algebraic Riccati equation (ARE) and the solution guarantees the ultimately uniform boundedness (UUB) of the local neighborhood error vector under conservative conditions. The law of parameters selection is summarized. The simulation results show that the proposed method can ensure that the local neighborhood error vectors converge asymptotically to the origin, that is, the multiple autonomous unmanned linear systems can achieve final synchronization, which demonstrates that the UUB of errors is conservative. Meanwhile, the bounded L_2 -gain condition for the coupling attenuation can be guaranteed.

This proposed method is suitable for the cooperative consensus control of various homogeneous multiple autonomous unmanned linear systems, such as an underwater robot swarm and aerial UAV swarm. Future work will focus on extending this method to nonlinear multi-agent systems and more serious models with uncertainties.

Author Contributions: Conceptualization, Y.L. and B.W.; methodology, Y.L.; software, Y.L.; validation, Y.L. and Y.C.; formal analysis, Y.C.; investigation, Y.L.; resources, B.W.; data curation, Y.L.; writing—original draft preparation, Y.L.; writing—review and editing, Y.L.; visualization, Y.L. and B.W.; supervision, B.W.; project administration, Y.C.; funding acquisition, B.W. All authors have read and agreed to the published version of the manuscript.

Funding: This research was funded by the National Natural Science Foundation of China (NSFC), grant number 51777058, and in part by the Six Talent Peaks Project in the Jiangsu province, grant number XNY-010.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Zhou, Y.; Li, D.; Gao, F. Optimal synchronization control for heterogeneous multi-agent systems: Online adaptive learning solutions. *Asian J. Control* **2021**. [\[CrossRef\]](#)
2. Jing, G.; Zheng, Y.; Wang, L. Consensus of Multiagent Systems With Distance-Dependent Communication Networks. *IEEE Trans. Neural Netw. Learn. Syst.* **2016**, *28*, 2712–2726. [\[CrossRef\]](#) [\[PubMed\]](#)
3. Liu, J.; Dai, M.-Z.; Zhang, C.; Wu, J. Edge-Event-Triggered Synchronization for Multi-Agent Systems with Nonlinear Controller Outputs. *Appl. Sci.* **2020**, *10*, 5250. [\[CrossRef\]](#)
4. Shi, H.; Hou, M.; Wu, Y. Distributed Control for Leader-Following Consensus Problem of Second-Order Multi-Agent Systems and Its Application to Motion Synchronization. *Appl. Sci.* **2019**, *9*, 4208. [\[CrossRef\]](#)
5. Vamvoudakis, K.G.; Lewis, F.L.; Hudas, G.R. Multi-agent differential graphical games: Online adaptive learning solution for synchronization with optimality. *Automatica* **2012**, *48*, 1598–1611. [\[CrossRef\]](#)
6. Vamvoudakis, K.G.; Lewis, F.L. Multi-agent differential graphical games. In Proceedings of the 30th Chinese Control Conference, Yantai, China, 22–24 July 2011.
7. Liu, J.; Xu, F.; Lin, S.; Cai, H.; Yan, S. A Multi-Agent-Based Optimization Model for Microgrid Operation Using Dynamic Guiding Chaotic Search Particle Swarm Optimization. *Energies* **2018**, *11*, 3286. [\[CrossRef\]](#)
8. Lowe, R.; Wu, Y.; Tamar, A.; Harb, J.; Abbeel, P.; Mordatch, I. Multi-agent actor–critic for mixed cooperative-competitive environments. *arXiv* **2017**, arXiv:1706.02275. [\[CrossRef\]](#)
9. Liu, Y.; Geng, Z. Finite-time optimal formation control of multi-agent systems on the Lie group SE(3). *Int. J. Control* **2013**, *86*, 1675–1686. [\[CrossRef\]](#)
10. Zhang, W.; Hu, J. Optimal multi-agent coordination under tree formation constraints. *IEEE Trans. Autom. Control* **2008**, *53*, 692–705. [\[CrossRef\]](#)
11. Lin, W.; Zhao, W.; Liu, H. Robust Optimal Formation Control of Heterogeneous Multi-Agent System via Reinforcement Learning. *IEEE Access* **2020**, *8*, 218424–218432. [\[CrossRef\]](#)
12. Arulkumaran, K.; Deisenroth, M.P.; Brundage, M.; Bharath, A.A. Deep Reinforcement Learning: A Brief Survey. *IEEE Signal Process. Mag.* **2017**, *34*, 26–38. [\[CrossRef\]](#)
13. Mnih, V.; Kavukcuoglu, K.; Silver, D.; Rusu, A.A.; Veness, J.; Bellemare, M.G.; Graves, A.; Riedmiller, M.; Fidjeland, A.K.; Ostrovski, G.; et al. Human-level control through deep reinforcement learning. *Nature* **2015**, *518*, 529–533. [\[CrossRef\]](#) [\[PubMed\]](#)
14. Vinyals, O.; Babuschkin, I.; Czarnecki, W.M.; Mathieu, M.; Dudzik, A.; Chung, J.; Choi, D.H.; Powell, R.; Ewalds, T.; Georgiev, P.; et al. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature* **2019**, *575*, 350–354. [\[CrossRef\]](#)
15. Levine, S.; Pastor, P.; Krizhevsky, A.; Ibarz, J.; Quillen, D. Learning hand-eye coordination for robotic grasping with deep learning and large-scale data collection. *Int. J. Robot. Res.* **2017**, *37*, 421–436. [\[CrossRef\]](#)
16. Tatari, F.; Vamvoudakis, K.G.; Mazouchi, M. Optimal distributed learning for disturbance rejection in networked non-linear games under unknown dynamics. *IET Control Theory Appl.* **2019**, *13*, 2838–2848. [\[CrossRef\]](#)
17. Jiao, Q.; Modares, H.; Xu, S.; Lewis, F.L.; Vamvoudakis, K.G. Multi-agent zero-sum differential graphical games for disturbance rejection in distributed control. *Automatica* **2016**, *69*, 24–34. [\[CrossRef\]](#)
18. Qin, J.; Li, M.; Shi, Y.; Ma, Q.; Zheng, W.X. Optimal Synchronization Control of Multiagent Systems With Input Saturation via Off-Policy Reinforcement Learning. *IEEE Trans. Neural Netw. Learn. Syst.* **2019**, *30*, 85–96. [\[CrossRef\]](#)
19. Kamalapurkar, R.; Walters, P.; Dixon, W. Model-Based Reinforcement Learning for Approximate Optimal Regulation. *Control. Complex Syst.* **2016**, 247–273. [\[CrossRef\]](#)
20. Farrell, J.A. Persistence of excitation conditions in passive learning control. *Automatica* **1997**, *33*, 699–703. [\[CrossRef\]](#)
21. Kamalapurkar, R.; Andrews, L.; Walters, P.; Dixon, W.E. Model-Based Reinforcement Learning for Infinite-Horizon Approximate Optimal Tracking. *IEEE Trans. Neural Networks Learn. Syst.* **2016**, *28*, 753–758. [\[CrossRef\]](#)
22. Yasini, S.; Karimpour, A.; Sistani, M.-B.N.; Modares, H. Online concurrent reinforcement learning algorithm to solve two-player zero-sum games for partially unknown nonlinear continuous-time systems. *Int. J. Adapt. Control Signal Process.* **2014**, *29*, 473–493. [\[CrossRef\]](#)
23. Vamvoudakis, K.G.; Lewis, F.L. Multi-player non-zero-sum games: Online adaptive learning solution of coupled Hamilton–Jacobi equations. *Automatica* **2011**, *47*, 1556–1569. [\[CrossRef\]](#)
24. Bucolo, M.; Buscarino, A.; Fortuna, L.; Frasca, M. LQG control of linear lossless positive-real systems: The continuous-time and discrete-time cases. *Int. J. Dyn. Control* **2022**, *10*, 1075–1083. [\[CrossRef\]](#)
25. Buscarino, A.; Fortuna, L.; Frasca, M.; Rizzo, A. Dynamical network interactions in distributed control of robots. *Chaos: Interdiscip. J. Nonlinear Sci.* **2006**, *16*, 015116. [\[CrossRef\]](#)
26. Khoo, S.; Xie, L.; Man, Z. Robust Finite-Time Consensus Tracking Algorithm for Multirobot Systems. *IEEE/ASME Trans. Mechatron.* **2009**, *14*, 219–228. [\[CrossRef\]](#)
27. Brewer, J. Kronecker products and matrix calculus in system theory. *IEEE Trans. Circuits Syst.* **1978**, *25*, 772–781. [\[CrossRef\]](#)