Supporting Information

for

Remarkably Facile Preparation of Superhydrophobic Functionalized

Bismuth Trioxide (Bi₂O₃) Coatings

Tao-tao Liang^{1,3}, Xiao-gang Guo^{2, 3, 4}*

¹Green Intelligence Environmental School, Yangtze Normal University, Chongqing 408100, China

²Chongqing Key Laboratory of Inorganic Special Functional Materials, College of Chemistry and Chemical Engineering, Yangtze Normal University, Chongqing 408100, China

³Faculty of Materials and Energy, Southwest University, Chongqing 400715, China

⁴College of Chemistry and Environmental Engineering, Institute of Functional Materials, Material Corrosion and Protection Key Laboratory of Sichuan Province, Sichuan University of Science and Engineering, Zigong 643000, China

* Correspondence: guoxiaogang0528@126.com




Figure S1. The particle size distribution of nano- Bi_2O_3

Table S1. Assembly efficiency comparison of different suspension agents.

Suspension agents	Particles concentration (g/L)	Assembly efficiency
Methanol	0.15-0.50	Low
Ethanol	0.15-0.50	Low
Isopropyl alcohol	0.15-0.50	Medium
Butanol	0.15-0.50	Low
Polyethylene glycol	0.15-0.50	Low
Pentanol	0.15-0.50	Low
Esters	0.15-0.50	Low
Aqueous solution	0.15-0.50	Low
Acetylacetone + Ethanol	0.15-0.50	Medium
Acetylacetone + Ethanol+ Polyethylene glycol	0.15-0.50	High