


Abstract

Corrosion Resistance of Aluminium against Salt Hydrates Used for Latent Heat Storage by Using Different Coating Materials †

Mayra Paulina Alferez Luna * , Franziska Klünder and Stefan Gschwander

Fraunhofer Institute for Solar Energy Systems ISE, Heidenhofstraße 2, 79110 Freiburg, Germany; franziska.kluender@ise.fraunhofer.de (F.K.); stefan.gschwander@ise.fraunhofer.de (S.G.)

* Correspondence: mayra.alferez.luna@ise.fraunhofer.de; Tel.: +49-761-4588-2016

† Presented at the First Corrosion and Materials Degradation Web Conference, 17–19 May 2021;

Available online: <https://cmdwc2021.sciforum.net/>.

Abstract: Thermal energy storage (TES) is required when using energy sources that are intermittent in order to fill the gap between energy supply and energy demand. Latent heat storage systems are based on phase change materials (PCM) such as salt hydrates, which absorb and release thermal energy with a change in its physical state. However, even though salt hydrates are widely used as PCM, they are potentially corrosive. Since PCM are normally encapsulated in containers, their compatibility with each other has to be assessed in order to create resistant containers. In this work, the corrosion resistance of aluminium against two different salt hydrates (SP24E and SP50) in a temperature range of 40 °C to 60 °C was tested. Furthermore, four coatings (anodized, electroless nickel-phosphorous, powder and KTL-cathodic dip) were used to enhance the aluminium corrosion protection. The method used was the immersion corrosion test. Signs of severe localized corrosion were found in uncoated and nickel-phosphorous-coated aluminium, while the anodized coated aluminium showed slight uniform corrosion. According to the calculated corrosion rates, uncoated aluminium is not recommended to be used for long-term applications when using SP24E as PCM, as well as nickel-phosphorous-coated aluminium when using either of the two tested salt hydrates.

Keywords: latent heat storage; phase change material; aluminium; coating; salt hydrate; corrosion rate



Citation: Alferez Luna, M.P.; Klünder, F.; Gschwander, S.

Corrosion Resistance of Aluminium against Salt Hydrates Used for Latent Heat Storage by Using Different Coating Materials. *Mater. Proc.* **2021**, *6*, 31. <https://doi.org/10.3390/CMDWC2021-10045>

Academic Editor: Raman Singh

Published: 14 May 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

Supplementary Materials: The conference presentation file is available at <https://www.mdpi.com/article/10.3390/CMDWC2021-10045/s1>.

Funding: This research was funded by the German Federal Ministry of Economic Affairs and Energy (BMWi), grant number 03ET1463A.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Data sharing is not applicable to this article.

Conflicts of Interest: The authors declare no conflict of interest.